

The multi-function Survivor Pivot USB provides budget-friendly rechargeability combined with a dual beam and 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.



Spot: High: 300 lumens; 369m beam distance; runs 4.25 hours (SL-B26); runs 5.5 hours (alk) Low: 70 lumens; 184m beam distance; runs 16 hours (SL-B26); runs 15 hours (alk)	
Flood: High: 300 lumens; 35m beam distance; runs 4.25 hours (SL-B26); runs 5.5 hours (alk) Low: 70 lumens; 17m beam distance; runs 16 hours (SL-B26); runs 15 hours (alk)	
Combo: High: 325 lumens; 276m beam distance; runs 3.75 hours (SL-B26); runs 4.5 hours (alk) Low: 80 lumens; 141m beam distance; runs 13 hours (SL-B26); runs 12 hours (alk)	
Non-Magnet: SL-B26: 15.8 oz (448 g)	Alkaline: 16.7 oz (473 g)
Magnet: SL-B26: 17.2 oz (488 g)	Alkaline: 18.1 oz (513 g)
Height: 7.93 in (20.14 cm); Width: 2.86 in (7.26 cm)	
Thickness: 3.29 in (8.36 cm); Thickness (w/ magnet): 3.64 in (9.25 cm)	

Unbreakable polycarbonate lens with scratch-resistant coating				
Class I & II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 (<i>Pending Approval</i>) Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)				
IP67-rated; dust-tight and waterproof to 1m for 30 minutes				
Limited Lifetime Warranty Visit streamlight.com for full warranty information				
Description	Orange w/o Magnet	Yellow w/o Magnet	Orange w/ Magnet	Yellow w/ Magnet
Survivor Pivot USB	91804	91814	91838	91839



SL-B26[®] LI-ION USB BATTERY PACK/ BANK CHARGER

PROTECTED LI-ION USB RECHARGEABLE BATTERY PACK
AND 8-UNIT BANK CHARGER

The battery pack that transforms multi-fuel, high-performance lighting tools into rechargeable systems.
Organize, store and charge your batteries with Streamlight's eight-unit bank charger.

SL-B26[®] protected Li-Ion USB rechargeable battery pack charges in 5 hours



Charge indicators over each battery slot
Red = charging, Green = charged

Charge bays securely hold batteries in place - ideal for mounting on trucks

Features charge status indicator



CHARGING

CHARGED

Charge via USB source or use a bank charger for departmental use



AC/DC power input

Low-profile (1"; 2.54 cm) - minimal mounting area

SL-B26 Battery Pack Specs:

SL-B26 protected Li-Ion rechargeable battery pack with built in Micro-USB charge port
Micro-USB input; charges in 5 hours; or charge with 8-unit bank charger
Integrated safety circuit protects battery from over-discharge/overcharge
2.75" (7 cm); 1.7 oz. (48g)
2 Year Limited Warranty Visit streamlight.com for full warranty information

ITEM	1PK	2PK	8PK
SL-B26 Battery Pack	#22101	#22102	#22105

Bank Charger Specs:

Charges up to eight batteries. Charge time: 5.25 hours
Impact-resistant polymer construction
Meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in upright position
10.45" x 4.74" x 1" (26.54 x 12.06 x 2.54 cm); 7.6 oz. (216g) w/o batteries; 20.88 oz. (592g) w/ batteries
Limited lifetime warranty Visit streamlight.com for full warranty information

ITEM	BOX
8-Unit Bank Charger - 120V/100V AC	#20221
8-Unit Bank Charger - 230V/240V AC	#20222
8-Unit Bank Charger - 12V DC	#20220
8-Unit Bank Charger - with batteries - 120V/100V AC	#20224
8-Unit Bank Charger - with batteries - 230V/240V AC	#20225
8-Unit Bank Charger - with batteries - 12V DC	#20223