

**ATEX and IECEx-rated for Category 1 (Zone 0) and Group IIC locations.
 For use in places with an explosive gas atmosphere (other than mines susceptible to firedamp) that is present continually or for longer periods.**



115 LUMENS
 175 TOTAL LUMEN OUTPUT

Three output modes: Spot, flood, both (spot and flood simultaneously): - Spot: 115 lumens; 3,100 candela; 111m beam distance; runs 24 hours - Flood: 115 lumens; 75 candela; 17m beam distance; runs 24 hours - Simultaneous spot beam and flood beam: 175 lumens; runs 15 hours Spot beam utilizes smooth parabolic reflector for tight beam with optimum peripheral illumination Flood beam produces a soft, wide beam to illuminate your work area
Spot and flood beams intersect for an uninterrupted light pattern to eliminate blind spots
One-handed operation of all lighting modes
Rocky stipple texture for a sure grip

IPX4 water-resistant; 2 meter impact resistance tested
Operating temperature: -20°F to 130°F. (To maintain hazardous locations rating: -20°C to 40°C)
II 1G Ex ia op is IIC T3/T4 Ga; FTZU 16ATEX0120X, IECEx FTZU 16.0022X
15.5 cm; 111g with AA alkaline batteries (included)
Limited Lifetime Warranty Visit www.streamlight.com for full warranty information
#67754 Dualie 2AA ATEX with two "AA" alkaline batteries - Box - Orange

