

**PROTAC® 90X USB // PROTAC® 90X**  
**MULTI FUEL - USB LI-ION RECHARGEABLE OR 2X CR123A FLASHLIGHT**

**DESCRIPTION:** The ProTac® 90X USB or ProTac® 90X are 1000-lumen tactical lights that can use either a proprietary Streamlight SL-B26® Li-Ion rechargeable battery pack or two CR123A disposable batteries. The **ProTac 90X USB** is a complete rechargeable system that comes with a charge cord and a USB Li-Ion button top battery pack that features an integrated micro-USB charge port. The **ProTac 90X** comes packaged with two CR123A batteries. Both lights feature a tactical switch for momentary or constant on operation, three different user selectable programs, and a pocket clip for convenience. The aluminum housing with Type II Military Spec anodizing helps make the lights extremely durable and abrasion resistant. Packaged with a removable pocket clip and holster.

**CASE MATERIAL:** 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black.

**DIMENSIONS:** Length: 4.39 in (11.1 cm) Head Diameter: 1.14 in (2.9 cm) Body Diameter: 0.940 in (2.4 cm)

**WEIGHT:** ProTac 90X USB: 4.9 oz (139 g) with one Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack.  
 ProTac 90X: 4.4 oz (125 g) with two CR123A batteries.

**LENS:** Glass lens; gasket sealed.

**LIGHT SOURCE:** LED technology, impervious to shock with a 50,000-hour lifetime.

**LIGHT OUTPUT:** See chart. Regulated output for consistent lumen performance over the battery life.

**ON/OFF:** Multi-function, push-button tactical switch. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch allows for user selection of one of three different programs: high/strobe/low (factory default), high only, or low/med/high.

**RUN TIME:** See charts for specific battery type. All run time claims are to 10% of initial lumen output.


**BATTERY:** One (1) Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack with on-board safety control, 2600mAh, Rechargeable up to 500 times. Recharges in 5 hours.  
 Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years.  
**WARNING - EXPLOSION RISK, BURN, AND FIRE HAZARD.** Do not use SL-B9™ batteries in firefighting apparatus or fire situations. Do not expose SL-B9™ battery to temperatures greater than 140 °F (60 °C).

**FEATURES:**











LED technology for extreme brightness.  
 IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.  
 2-meter impact resistance tested.  
 Multi fuel; accepts Streamlight SL-B26® or CR123A batteries.  
 TEN-TAP® programmable; allows user to select one of three different programs.  
 Anti-roll face cap.  
 Serialized for positive identification.  
 Removable pocket clip and holster

**APPROVALS:**  Meets applicable United Kingdom and European Community Directives.

 CEC Compliant (ProTac 90X USB only)

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL ACCESSORIES:** Holster, charge cords

	CR123A BATTERIES				SL-B26® LI-ION BATTERY PACK					
	FL1 STANDARD	HIGH	MEDIUM	LOW	FL1 STANDARD	HIGH	MEDIUM	LOW		
<b>OUTPUT</b>		1,000 LUMENS	300 LUMENS	65 LUMENS		1,000 LUMENS	300 LUMENS	65 LUMENS		
<b>RUN TIME</b>		2h 30min	4h	21h		1h 45min	4h 45min	24h		
<b>DISTANCE</b>		171m	91m	42m		171m	91m	42m		
<b>INTENSITY</b>		7,350cd	2,060cd	450cd		7,350cd	2,060cd	450cd		
		Strobe Run Time: 2.5 hours					Strobe Run Time: 3.5 hours			

