



Material/Lens Impact-resistant engineering resin case offering exceptional durability and weather resistance. All openings are O-ring sealed. Unbreakable polycarbonate lens.

Dims/Weight Facecap diameter: 1.88 in. (4.76 cm); Maximum Headlight Width: 2.50 in. (6.35 cm); Maximum Headlight Length: 3.08 in. (7.82 cm); 4.5 ounces (128 grams); 7.1 ounces; 202 grams (with batteries.)

Light Source White LED, impervious to shock with a 50,000 hour lifetime.

Output/Runtime 270 lumens; 5,600 candela; 150m beam; runs 8 hours.

Switch Push button switch; On, Off. Easy operation even when wearing heavy gloves.

Battery Three "AA" alkaline batteries (included)

- Features**
- Parabolic reflector produces long range brilliance and smooth uniform beam pattern
 - Impact-resistant housing - drop-test verified; 1 meter impact resistance tested
 - Rubber hard hat strap and elastic strap
 - 90 degree tilting head

Approvals ATEX: II 1G Ex ia IIC T3 Ga – FTZU 11 ATEX 0052X
IECEX: Ex ia op is IIC T3 Ga; UL-BR 12.0403X
Meets Applicable United Kingdom and European Community Directives



Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Item	UPC	Part #
3AA HAZ-LO - ALK BATTs, ELASTIC & RUBBER STRAPS - ATEX - Orange	080926-61250-1	61250
3AA HAZ-LO - ALK BATTs, ELASTIC & RUBBER STRAPS - INMETRO - Orange	080926-61251-8	61251

Assembled in the USA