

Increased output with added features, the C1D1 safety rated Survivor X right-angle light is available as a fully rechargeable system or an economical alkaline model that provides a 25% cost savings on batteries.




Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation





New charger design:

- Survivor X securely locks into the charger fits snugly in place
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



- High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; runs 3.75 hours (Li-lon); runs 5 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 15 hours (Li-lon); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours

Optimized electronics provide regulated intensity

IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested

Uses rechargeable lithium ion battery (charges in 5 hours) or three alkaline batteries

7.06 in. (17.92 cm); Li-Ion: 12.2 oz (346g); Alkaline: 12.8 oz (363g)

Class I & II, Division 1, Groups A, B, C, D,E, F, G; Class III, T-Code: T3/T4

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

Limited Lifetime Warranty

Visit streamlight.com for full warranty information

	ORANGE	YELLOW	DESCRIPTION
ſ	90953	90963	Survivor X - 230V AC/12V DC
	90952	90962	Survivor X - 120V/100V AC/12V DC
	90950	90960	Survivor X - Alkaline