

## PRODUCT FACT SHEET

## ProTac HL®4 HIGH LUMEN LITHIUM TACTICAL FLASHLIGHT

**MARKET** 

APPLICATIONS: Law Enforcement, Security, Emergency Medical Services, Sporting Goods, Hardware/Tool, Consumer

**DESCRIPTION:** With 2,200 lumens of blinding light, the ProTac HL®4 is the newest and brightest addition to the

ProTac® series. The ProTac HL®4 offers the latest in power LED technology and three different user selectable programs. The light will accept two battery types, four CR123A batteries or two of Streamlight's SL-B26™ protected Li-Ion USB rechargeable batteries. The output from the LED results in one of the brightest tactical lights available. The "sure grip rubber sleeve" and included lanyard

ensures you'll never lose your grip.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

**DIMENSIONS:** Length: 8.63 in. (21.92 cm) Barrel Diameter: 1.24 in. (3.15 cm)

Head Diameter: 2.35 in. (5.97 cm)

Tri-Lobe Diameter: 2.29 in. (5.81 cm)

**WEIGHT:** 1 lb 1 oz (482 grams) with CR123A batteries. 1 lb 2 oz (510 grams) with SL-B26™ Li-Ion batteries.

**LENS:** Glass lens with anti-reflective coating, gasket sealed.

**LIGHT SOURCE:** LED technology, impervious to shock with a 50,000 hour lifetime. Total internal reflection optic.

**LIGHT OUTPUT:** See charts. Optimized electronics provides thermal management and regulated intensity.

ON/OFF: Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable

intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three

different programs: high/strobe/low (factory default), high only, or low/med/high.

**RUN TIME:** See chart. All claims to 10% of initial lumen output.

**BATTERY:** Four (4) 3 Volt CR123A Lithium batteries, (CR123A batteries have a shelf life of 10 years) or two

Streamlight® SL-B26™ protected Li-Ion USB rechargeable batteries with on-board safety control,

2600mAh, rechargeable up to 500 times. Recharges in 5 hours.

**EATURES:** LED technology for extreme brightness.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

1 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life. TEN-TAP® programmable switch allows user to select one of three different programs.

Anti-roll facecap.

Sure grip rubber sleeve.

Serialized for positive identification.

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**APPROVALS:** CE Meets applicable European Community directives.

**OPTIONAL** 

ACCESSORIES: Holster

## WITH CR123A BATTERIES

1	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT	31/2	2200 LUMENS	600 LUMENS	60 LUMENS
RUNTIME	$\Theta$	1h 30min	4h	40h
DISTANCE		346m	182m	56m
INTENSITY		30000cd	8300cd	800cd

Strobe Runtime: 2.5 hours

## WITH SL-B26™ RECHARGABLE BATTERIES

FL1 STANDARD	HIGH	MEDIUM	LOW
31/2	2200 LUMENS	600 LUMENS	60 LUMENS
0	1h 45 min	4h 15 min	43h
	346m	182m	56m
	30000cd	8300cd	800cd

Strobe Runtime: 3.5 hours

Issued: 1/7/2016