



# PRODUCT FACT SHEET

## STREAMLIGHT SURVIVOR® - DIVISION 2

### MARKET

APPLICATIONS: Fire & Rescue, Law Enforcement, Industrial Safety, Public Works & Utilities, Marine

DESCRIPTION: The Survivor is a lightweight, hand-held light with right angle head designed for use in hazardous locations.

CASE MATERIAL: Lamp housing, battery housing and battery base are made from high impact super tough nylon, offering exceptional durability and weather resistance. All openings are "O" ring sealed. Spring loaded clip with built in attachment ring attaches to belts and harnesses. One way valve for case venting. Available in international safety orange or high visibility yellow.

DIMENSIONS: Height: 6.75 in. (17.15 cm) Width: 2.85 in. (7.24 cm) Diameter: 2.87 in. (7.29 cm)  
Height in charger: 8.50 in. (21.6 cm)  
Grip area: Height: 3.6 in. (9.14 cm) Width: 2.20 in. (5.59 cm) Thickness: 1.35 in. (3.43cm)

WEIGHT: 15.4 oz (437 grams)\*

LENS: Unbreakable Polycarbonate Lens with silicone anti-scratch coating is assembled in a heavy duty bezel.  
"O" ring sealed.

LIGHT SOURCE: 5.5-watt, black-dot xenon bulb with anti-glare coating has an average life of up to 50 hours and provides maximum visibility in smoke and fog with less glare, scatter and bounce back.

LIGHT OUTPUT: Up to 25,000 Peak beam candlepower. Bulb Rating: 114 Lumens typical

ON/OFF: "O" ring sealed rotary switch made from flame retardant glass-filled thermoplastic. A 1/4" high actuator provides easy operation even when wearing heavy gloves.

RUN TIME: Operational for up to 1.70 continuous hours between charges.

BATTERY: Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C can be recharged up to 1,000 times. Spare battery pack can be speed-loaded in seconds into the light via a hinged door with stainless steel latch.

CHARGE OPTIONS: AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources. The universal Steady Charger, which requires up to 10 hours for a complete charge, can be used with 110V, 120V, 230V, 240V, or 12V DC by exchanging its charge cord. All chargers are available with "Piggy Back" battery cartridge charger that allows charging of both flashlight and spare battery simultaneously.

FEATURES: Serialized for positive identification

APPROVALS\*\*: UL Listed for Class I, II, III, Division 2, Groups A, B, C, D, F, G  
CUL Listed for Class I, II, III, Division 2, Groups A, B, C, D, F, G  
Rack meets requirements of NFPA 1901-12.17 mounted in any position. **NFPA**  
Most models meet applicable European Community Directives. **CE**

WARRANTY: Limited lifetime warranty.

OPTIONAL ACCESSORIES: Steady charge 5-Unit bank charger.

\* With battery (included in purchase)  
\*\* See product for specific ratings.

Assembled In The USA.