



TLR-1® / TLR-1®s
RAIL MOUNTED TACTICAL LIGHT OR STROBING TACTICAL LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Military, Home Defense

DESCRIPTION: Lightweight, compact, lithium battery powered Gun-Mounted Tactical Light featuring the latest in shock-proof power LED technology and providing at least 2.5 hours of continuous run time. Rail clamp designed to rapidly attach/detach from side of weapon. Both models offer a tethered battery door and latch mechanism that prevents battery door loss while providing easy battery replacement. Strobe activated on two or more momentary paddle hits for guaranteed entry into strobe mode (TLR-1®s only).

CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish.

DIMENSIONS: Length: 3.26 in. (8.28 cm) Width: 1.47 in. (3.73 cm) Height: 1.44 in. (3.65 cm)

WEIGHT: 4.18 oz (118.6 grams) with batteries (included in purchase).

LENS: High temperature, shock mounted, impact resistant Boro Float glass.

LIGHT SOURCE: C4®LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: 8,000 candela peak beam intensity and 160 lumens measured system output. Deep-dish parabolic reflector produces a concentrated beam with optimum peripheral illumination.

ON/OFF: Ambidextrous momentary/steady On-Off switch.
Double tap of momentary paddle within 0.4 seconds activates strobe. (TLR-1®s only)

RUN TIME: 2.5 hours regulated run time. Solid-state current regulation for consistent illumination level.

BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES: C4®LED technology
Ambidextrous momentary/steady On-Off switch.
One handed snap-on/tighten interface keeps hands away from muzzle when attaching/detaching.
Securely fits a broad range of weapons.
Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails.
Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW.
Extensively live-fire tested impact resistant construction.
Operating temperature: -40°F to +120°F.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Strobe mode (TLR-1®s only)

APPROVALS: Meets applicable European Community Directives. **CE**

WARRANTY: Streamlight warrants this product to be free of defect for a lifetime of use. We will repair, replace or refund the purchase price, at our option, of any Streamlight product that does not work as a result of a manufacturing defect for as long as you own it. Of course, this limited lifetime warranty excludes abuse, batteries and normal wear and tear.

OPTIONAL

ACCESSORIES: Mounting Adapters, Remote Switches, Filters