



PRODUCT FACT SHEET

STREAMLIGHT MICROSTREAM LED FLASHLIGHT

MARKET APPLICATIONS: Automotive, Hardware/Tool, Industrial, Law Enforcement, Security, Sporting Goods, Consumer.

DESCRIPTION: Weighing just over 1 ounce (w/ battery) and ready for the demands of professional use, the ultra-compact 0.5 Watt LED Micro Stream runs on a single AAA battery. Developed for multiple tasks across all markets, the hallmarks of this light are its compact durable construction, optimum beam output and a tailcap switch for single-handed operation. The Micro Stream is machined from solid aircraft-grade aluminum alloy and is plated with a MIL-Spec Type II anodize finish providing excellent abrasion and corrosion resistance. The Micro Stream also incorporates an internal polymer body liner and shockproof switch housing allowing for operation under the most extreme conditions. The light has been drop test verified above the industry standard of six feet and extensively field tested. The Micro Stream incorporates an unbreakable polycarbonate lens and multiple O-ring design providing water resistant construction and contamination resistance. Utilizing the latest 0.5 Watt emitter technology and Streamlight's proprietary *Micro Optical System (MOS)*, Streamlight engineers have produced this ultra compact and light weight flashlight with optimized output and run time. The durometer of the rubber used for the tailcap switch boot has been chosen for superior tactile feel and designed to keep out any foreign matter.

CASE MATERIAL: Corrosion and water resistant, machined aircraft-grade aluminum alloy, Type II MIL-Spec anodize plating. Available in matte black finish.

DIMENSIONS: Length: 3.5 inches (90 mm) Body Diameter: 0.6 inches (15 mm)

WEIGHT: 1.04 oz. (29.7 grams) with battery* (* AAA Panasonic battery included with purchase)

LENS: Unbreakable and scratch resistant polycarbonate lens

LIGHT SOURCE: 0.5 Watt High-Flux LED; 30,000 hours rated LED life

LIGHT OUTPUT: Up to 20 Lumens Typical

ON/OFF: Push Button Tail switch

RUN TIME: Up to 1.5 hours of regulated runtime

BATTERY: One (1) "AAA" alkaline battery

FEATURES: Tailcap switch for momentary On/Off.
O-Ring Sealed, shock proof and drop tested construction
Water resistant per IPX4; in accordance with specification EN 60529:1992
High Strength "Break Away" safety lanyard.
Unbreakable pocket clip

APPROVALS: Most models meet applicable European Community Directives.

WARRANTY: Limited lifetime warranty



Made In China.