

Survivor® LED Flashlight

Case Material: Housing, base and battery housing made from high impact super tough nylon, offering exceptional durability and passes a 30 Ft drop test. All openings are O-ring sealed for weather resistance. Spring loaded clip with built in ring easily attaches to belts and harnesses. One way valve for case venting. Available in international safety orange, high visibility yellow or black.

Dimensions: Height: 7.06 in. (17.92 cm) Height in charger: 8.50 in. (21.6 cm)
 Width: 2.85 in. (7.24 cm) Diameter: 2.87 in. (7.29 cm)

Grip area:

Height: 3.6 in. (9.14 cm) Thickness: 1.35 in. (3.43cm) Width: 2.20 in. (5.59 cm)

Weight: NiCd: 17.9 oz (508 grams)*, Alkaline: 13.1 oz (371 grams)*

Lens: Unbreakable polycarbonate with silicone anti-scratch coating is assembled in a heavy duty bezel. O-ring sealed.

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime

Light Output: High: 21,000 candela peak beam intensity and 100 lumens measured system output.

Low: 7,500 candela peak beam intensity and 32 lumens measured system output.

Deep-dish parabolic reflector produces narrow beam; ideal for smoke-cutting applications. Optimum peripheral illumination to aid in navigation.

On/Off: Raised push-button switch for easy use with gloves. 3-position switch: high, low, locator strobe light

Run Time: NiCd: High: 3.5 continuous hours to the 10% output level. Low: 10+ hours. Flash: 7+ hours.

Alkaline: High: 4 continuous hours to the 10% output level. Low: 14+ hours. Flash: 7+ hours.

Battery: Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C can be recharged up to 1,000 times. Optional four (4) "AA" alkaline non-rechargeable battery pack provides fast replacement with readily available batteries.

Charging: AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources.

- Features:**
- Rechargeable model fits all existing Survivor charging units and accepts existing batteries
 - Microprocessor controls 2 levels of brightness - high/low beam and flash
 - Water resistant

Approvals:** UL Listed Class I, Division 1, Groups C & D; Class I, Division 2, Groups A, B, C, D;
 Class II, Division 2, Groups F & G; Class III, Temperature Code: T4
 UL-Canada Listed Class I, Division 1, Groups C & D, Exia; Class I, Division 2, Groups A, B, C, D;
 Class II, Division 2, Groups F & G; Class III, Temperature Code: T4
 Charger meets requirements of NFPA 1901-12-1.7 mounted in any position. **NFPA**
 Most models meet applicable European Community Directives. **CE**

Warranty: Limited lifetime warranty.

*With battery (included in purchase)

** See product for specific ratings.



Item	UPC	Part #
Steady Charge with AC/DC charger/holder		
Survivor LED 230V - Yellow	080926-90515-3	90515
Survivor LED 240V - Yellow	080926-90516-0	90516
Survivor LED 120V - Yellow	080926-90513-9	90513
Survivor LED 100 - Yellow	080926-90517-1	90517
Survivor LED 230V - Orange	080926-90505-4	90505
Survivor LED 230V - Orange (ATEX)	080926-90548-1	90548
Survivor LED 240V - Orange	080926-90506-1	90506
Survivor LED 240V - Orange (ATEX)	080926-90549-8	90549
Survivor LED 120V - Orange	080926-90503-0	90503
Survivor LED 100V - Orange	080926-90507-8	90507
Survivor LED 100V - Orange (ATEX)	080926-90550-4	90550
Survivor LED 230V - Black	080926-90525-2	90525
Survivor LED 240V - Black	080926-90526-9	90526
Survivor LED 120V - Black	080926-90523-8	90523
Survivor LED 100V - Black	080926-90527-6	90527

Item	UPC	Part #
Fast Charge with AC		
Survivor LED 230V - Yellow	080926-90514-6	90514
Survivor LED 120V - Yellow	080926-90512-2	90512
Survivor LED 230V - Orange	080926-90504-7	90504
Survivor LED 230V - Orange (ATEX)	080926-90551-1	90551
Survivor LED 120V - Orange	080926-90502-3	90502
Survivor LED 230V - Black	080926-90524-5	90524
Survivor LED 120V - Black	080926-90522-1	90522
Fast Charge with DC		
Survivor LED - Yellow	080926-90519-1	90519
Survivor LED - Orange (ATEX)	080926-90552-8	90552
Survivor LED - Black	080926-90528-3	90528
Survivor LED - Orange	080926-90509-2	90509
Without Charger		
Survivor LED - Yellow	080926-90510-8	90510
Survivor LED - Orange	080926-90500-7	90500
Survivor LED - Orange (ATEX)	080926-90553-5	90553
Survivor LED - Black	080926-90520-7	90520
Alkaline Model		
Survivor LED - Yellow	080926-90541-2	90541
Survivor LED - Orange	080926-90540-5	90540
Survivor LED - Orange (ATEX)	080926-90555-9	90555
Survivor LED - Black	080926-90529-0	90529
See reverse for additional part numbers		





Item	UPC	Part #
DC2 direct wire charge cord (All Rechargeables)	080926-22050-8	22050
DC1 Charge Cord (All Rechargeables)	080926-22051-5	22051
120V AC charge cord	080926-22311-0	22311
240V AC charge cord	080926-22241-0	22241
230V AC charge cord	080926-22664-7	22664
100V AC charge cord	080926-22666-1	2266
Steady Charge (SC) Plug-In Charger Holder **Cords not included	080926-90010-3	90010
AC Fast Charger (Includes Holder)	080926-90011-0	90011
DC #1 Fast Charger (Includes Holder)	080926-90012-7	90012
DC #2 Fast Charger (Includes Holder)	080926-90013-4	90013
Steady Charge (SC) PiggyBack® Charger **Cords not included	080926-90110-0	90110
AC PiggyBack® Fast Charger	080926-90111-7	90111
DC #1 PiggyBack® Fast Charger	080926-90112-4	90112
DC #2 PiggyBack® Fast Charger	080926-90113-1	90113
Battery Pack Assembly (Blue Sleeve, NiCd Battery)	080926-90130-8	90130
Bank Charger (SC) 120V AC	080926-90400-2	90400
Bank Charger DC	080926-90401-9	90401
Survivor LED alkaline battery pack (Batteries not included)	080926-90542-9	90542

