

PolyStylus® Alkaline Battery-Powered Polymer Pen Light



Case Material: Ultra-tough “FiberWrap™” fiberglass epoxy body resists bending or flexing, available in black.

Dimensions/Weight: Length: 6.68 in. (16.97 cm) Diameter: Major Diameter: 0.59 in. (1.50 cm) Body Diameter: 0.41 in. (1.04 cm)
1.4 oz (40 grams)*

Light Source: High intensity 5mm LED, impervious to shock with a 100,000 hour lifetime.
LED available in White, Blue (470nm), Red (624nm) or Green (527nm).

Light Output: White: 85 candela peak beam intensity; 9 lumens measured system output; 18, beam distance
Blue: 63 candela peak beam intensity; 1.7 lumens measured system output; 16m beam distance
Red: 72 candela peak beam intensity; 5.1 lumens measured system output; 17m beam distance
Green: 45 candela peak beam intensity; 3.5 lumens measured system output; 13m beam distance
Color coordinated parabolic reflector produces a concentrated beam with optimum peripheral illumination.

On/Off: Tailswitch offers one-handed momentary or constant “on” operation. Design tested for long life; verified at 100k+ actuations.

Run Time: White, Blue or Green: 48 hours to the 10% lumen output level. Red: 24 hours to the 10% lumen output level.

Battery: 3 “AAAA” size alkaline batteries.

- Features:
- Interchangeable colored LED modules
 - IPX4; water-resistant
 - Integral pocket clip on endcap
 - Serialized for positive identification

Approvals**: Meets applicable European Community Directives



Intrinsic Safety for Haz. Loc. Class I, Div. 1, Groups C, D; Class II, Div. 1, Groups E,F,G; Class III, T-code: T4 “Classified”



Intrinsic Safety for Haz. Loc. Class I, Div. 1, Groups C, D; Class II, Div. 1, Groups E, F, G; Class III, T-code: T4 “Exia

FTZU 09 ATEX 0141 II 1G Ex ia IIB T4

Warranty: Limited lifetime warranty.

*With battery (included in purchase).

**See product for specific ratings.

Item	UPC	Part #
<i>English Packaging</i>		
PolyStylus Black. Blister packaged - White LED	080926-66401-2	66401
PolyStylus Black. Blister packaged - Green LED	080926-66403-6	66403
PolyStylus Black. Blister packaged - Blue LED	080926-66404-3	66404
PolyStylus Black. Blister packaged - Red LED	080926-66405-0	66405
PolyStylus Black. Blister packaged - Combo LED Pack	080926-66406-7	66406
<i>See reverse for additional part numbers</i>		





Item	UPC	Part #
<i>Multilingual packaging</i>		
PolyStylus Black. Blister packaged - White LED	080926-66401-2	66401
PolyStylus Black. Blister packaged - Green LED	080926-66403-6	66403
PolyStylus Black. Blister packaged - Blue LED	080926-66404-3	66404
PolyStylus Black. Blister packaged - Red LED	080926-66405-0	66405
PolyStylus Black. Blister packaged - Combo LED Pack	080926-66406-7	66406
PolyStylus Black. Blister packaged - White LED (ATEX)	080926-66421-0	66421
PolyStylus Black. Blister packaged - Green LED (ATEX)	080926-66423-4	66423
PolyStylus Black. Blister packaged - Blue LED (ATEX)	080926-66424-1	66424
PolyStylus Black. Blister packaged - Red LED (ATEX)	080926-66425-8	66425
PolyStylus Black. Blister packaged - Combo LED Pack (ATEX)	080926-66426-5	66426
PolyStylus - White LED Module	080926-66411-1	66411
PolyStylus - Green LED Module	080926-66413-5	66413
PolyStylus - Blue LED Module	080926-66414-2	66414
PolyStylus Red LED Module	080926-66415-9	66415
AAAA Batteries - 6 pack	080926-65030-5	65030

