

Stinger® LED HP Rechargeable Flashlight

FL 1 STANDARD	HIGH	MEDIUM	LOW
	200 LUMENS	100 LUMENS	50 LUMENS
	2h	3h 45min	7h 15min
	438m	309m	209m
	48,000cd	24,000cd	11,000cd
	3m	3m	3m

Strobe mode: Runs 5.5 hours
Product is tested per ANSI/NEMA FL-1 2009 standard



There is a real need to cut costs wherever possible, yet we cannot afford to forget about environmental issues. Streamlight high power rechargeable LED flashlights make good economic environmental sense. Over time they cost significantly less to operate decreasing the amount of batteries used, relieving the problem of battery disposal.

With Streamlight LED rechargeable flashlights, your company will not only save on the cost of batteries. Since LEDs have a long life and won't burn out or won't break, they never need to be replaced. Your light will always be ready when you need it.

More powerful and more economical, Streamlight rechargeable LED lighting tools pack a lot more power with ultra-bright white beams and long illumination times. They are more dependable and more cost-efficient than a "D" cell flashlight.

Case Material: 6000 series machined aircraft aluminum with non-slip rubberized comfort grip. Unbreakable polycarbonate lens with scratch-resistant coating

Dims/Weight: Length: 9.23 in. (23.44 cm); Body Diameter: 1.17 in. (2.97 cm); 13.6 oz (385 grams)

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime. Deep-dish parabolic reflector produces a long range targeting beam with optimum peripheral illumination to aid in navigation. Optimized electronics provide regulated intensity.

On/Off: Multi-function, easy access head mounted push-button switch designed for extremely long life; tested at 1 million actuations

Battery: 3-Cell, 3.6-Volt NiCd sub-C battery is rechargeable up to 1000 times
3-cell, 3.6 Volt Ni-MH sub-C battery, rechargeable up to 1000 times offered in 230V AC and 12V DC European systems

Charging: Steady charger fully recharges in 10 hours on 100V, 120V, 230V or 240VAC, or 12VDC. 2.5 hour fast charger or PiggyBack® charger models available.

Features:

- IPX4 Rated for water resistant operation
- LED Charge-continuity indicator on charger base
- Serialized for positive identification.
- 3 meter impact resistance tested
- Compact, snap-in charger mounts in any position

Approvals**: Meets applicable European Community Directives

Warranty: Streamlight's Limited Lifetime Warranty warrants this product to be free of defect, including the LED, for a lifetime of use. We will repair, replace or refund the purchase price, at our option, of any Streamlight product that does not work as a result of a manufacturing defect for as long as you own it. This limited lifetime warranty excludes abuse, batteries, chargers, switches, electronics and normal wear and tear. Rechargeable batteries, chargers, switches and electronics have a two (2) year warranty with proof of purchase.

**With battery (included in purchase).
Assembled in USA of US and foreign parts
All performance claims to ANSI/NEMA FL-1-2009 Standard*

Item #	Description	UPC
<i>Steady Charge</i>		
75775	Stinger LED HP 230V AC/12V DC	080926-75775-2
75763	Stinger LED HP 120V AC/12V DC	080926-75763-9
75774	Stinger LED HP 230V AC	080926-75774-5
75761	Stinger LED HP 120V AC	080926-75761-5
75757	Stinger LED HP 100V AC	080926-75757-8
75762	Stinger LED HP 12V DC	080926-75762-2
75760	Stinger LED HP W/O Charger	080926-75760-8
<i>Steady Charge PiggyBack</i>		
75782	Stinger LED HP 120V AC/12V DC PiggyBack	080926-75782-0
75783	Stinger LED HP 120V AC SC PiggyBack	080926-75783-7

Item #	Description	UPC
<i>Fast Charge</i>		
75781	Stinger LED HP 240V AC/12V DC Fast Charge	080926-75781-3
75785	Stinger LED HP 120V AC/12V DC Fast Charge	080926-75785-1
75764	Stinger LED HP 120V AC Fast Charge	080926-75764-6
75769	Stinger LED HP 100V AC Fast Charge	080926-75769-1
<i>Fast Charge PiggyBack</i>		
75756	Stinger LED HP 120V AC/12V DC Fast Charge PiggyBack	080926-75756-1
75786	Stinger LED HP 120V AC Fast Charge PiggyBack	080926-75786-8
<i>See reverse for additional part numbers</i>		





Item Description - NiMH Configurations	UPC	Part #
Stinger LED HP 230V AC/12V DC NiMH Battery	080926-75982-4	75982
Stinger LED HP 230V AC NiMH Battery	080926-75981-7	75981
Stinger LED HP 12V DC NiMH Battery	080926-75799-8	75799
Stinger LED HP (WITHOUT CHARGER) NiMH battery	080926-75980-0	75980

Item	UPC	Part #	
DC2 direct wire charge cord	080926-22050-8	22050	
DC1 Charge Cord	080926-22051-5	22051	
120V AC charge cord	080926-22311-0	22311	
100V AC charge cord	080926-22666-1	22666	
230V AC charge cord	080926-22664-7	22664	
240V AC charge cord	080926-22241-0	22241	
Charger Holder Stinger (10 Hour)	080926-75100-2	75100	
Charger Holder Fast Charge (2.5 hour)	080926-75103-3	75103	
5 Unit Bank Charger, 120V	080926-75400-3	75400	
5 Unit Bank Fast Charger, 120V	080926-75401-6	75401	
5 Unit Bank Charger, 230V	080926-75600-7	75600	
5 Unit Bank Fast Charger, 230V	080926-75601-4	75601	
5 Unit Bank Charger, 100V	080926-75700-4	75700	
5 unit bank charger 100V	080926-75701-1	75701	
Battery Stick (NiCd)	080926-75175-0	75175	
Battery Stick (NiMH)	080926-75375-4	75375	
PiggyBack® Charger Holder - Steady Charger & Battery	080926-75275-7	75275	
PiggyBack® Charger Holder Fast Charge & Battery	080926-75276-4	75276	
Safety Wand	Blue	080926-75947-3	75947
Safety Wand	Red	080926-75946-6	75946
Safety Wand	Yellow	080926-75948-0	75948
Safety Wand	White	080926-75949-7	75949
Safety Wand	Glow in the Dark	080926-75950-3	75950
Holster, (Deluxe Nylon)		080926-75909-1	75909
Ring Holder		080926-75906-0	75906
Holster (Nylon)		080926-76090-5	76090
Loop holster		080926-75928-8	75928

