

RECHARGEABLE LIGHTING SYSTEMS
EXPERIENCE THE COST SAVINGS



STREAMLIGHT®

TRANSFORM YOUR HIGH-PERFORMANCE LIGHTING TOOLS

INTO RECHARGEABLE SYSTEMS THAT OUTSHINE AND OUTPERFORM FLASHLIGHTS WITH TRADITIONAL BATTERY PLATFORMS

AND SAVE MONEY IN THE PROCESS!

STREAMLIGHT OFFERS A LINE OF MULTI-FUEL LIGHTING TOOLS that accept either CR123A lithium batteries or SL-B26® protected Li-Ion USB-C rechargeable battery packs. Choosing a rechargeable flashlight system nearly eliminates battery replacement and recycling costs, while dramatically decreasing downstream waste.

- Our “X” SERIES of products provide the perfect blend of performance, durability and cost savings.

If you replace one pair of CR123A batteries each week for 52 weeks, that's 104 disposable batteries per year vs. a single SL-B26 rechargeable battery pack. If your organization has 100 lights in service, the SL-B26 rechargeable system could keep 10,400 batteries out of the waste stream and save your organization tens of thousands of dollars!

- Streamlight's proprietary SL-B26 battery packs feature an integrated safety circuit that protects from overcharge/overdischarge. They charge in 5 hours or less and feature a charge status indicator.
- A variety of power sources can be used to charge this battery platform including USB power cords, charge cradle or bank charger, portable power pack or 12V DC automotive power.
- The rechargeable capabilities of the SL-B26 battery pack gives you an easy field replaceable battery system providing one to use and a fully recharged back-up.



SL-B26 battery packs in eight unit bank charger

STREAMLIGHT, THE TRUSTED BRAND FOR ALL OF YOUR PROFESSIONAL AND PERSONAL LIGHTING NEEDS

#ToolsNotToys
#StreamlightStrong
#OftenImitatedbutNEVERDuplicated

RECHARGEABLE LIGHTING SYSTEMS

SL-B26[®] Lithium-Ion Battery Pack
pages 4-5



Survivor[®] Pivot[®]
see page 6



Survivor[®] X
see page 6



Stinger[®] 2020
see page 7



Siege[®] X USB
see page 7



ProTac[®] 2L-X USB
see page 8



ProTac[®] HL-X USB
see page 8



ProTac[®] 90X USB
see page 9



ProTac HL[®] 5-X USB
see page 9



PolyTac 90[®] X USB
see page 10



PolyTac[®] X USB
see page 10



Vantage[®] 180 X USB
see page 10



ProTac[®] Rail Mount HL-X Pro
see page 11



ProTac[®] Rail Mount HL-X USB
see page 11



ALSO WORKS WITH:

BATTERY SOLD SEPARATELY (NOT AVAILABLE AS SYSTEM)

ProTac HL[®] USB Headlamp
see page 13



ProTac HL[®] USB
see page 13



ProTac[®] HPL USB
see page 13



MULTI-FUEL FLEXIBILITY

A NEW WAY TO LOOK AT BATTERIES AND RECHARGEABILITY

THE FLEXIBILITY TO POWER YOUR LIGHT WITH...



OR



SL-B26[®] PROTECTED LITHIUM-ION USB RECHARGEABLE BATTERY PACK

The battery that transforms multi-fuel, high-performance lighting tools into rechargeable systems.

USB rechargeable - Features micro-USB input and charge status indicators; charges in 5 hours. Integrated safety circuit protects battery from overcharge.

Charge via USB source or optional charge cradle - or bank charger for departmental use. The charge cradle is ideal for storage as well as to charge your batteries.

BATTERY CAPACITY: 2600mAh SL-B26 protected

Li-Ion USB rechargeable battery pack

BATTERY SIZE: 2.75 in. x 0.744 in. (7 x 1.89 cm)

BATTERY WEIGHT: 1.7 oz. (48g)

CRADLE SIZE: 4.5 in. (11.4 cm)

CRADLE WEIGHT: 2.4 oz. (68g)



Features integrated USB port.

Charge status LEDs:

Red = charging

Green = charged



CHARGING



CHARGED

ITEM #	DESCRIPTION
22101	SL-B26 Li-Ion USB Rechargeable Battery Pack - 1pk
22105	SL-B26 Li-Ion USB Rechargeable Battery Pack - 8pk
22100	Li-Ion Charge Cradle
22010	Li-Ion Battery Pack Kit - Includes USB cord and (2) SL-B26 battery packs
22011	Li-Ion Battery Pack Kit - 120V AC - Includes (2) SL-B26 battery packs
22070	40 in. (101 cm) USB cord
22081	22 in. (55.88 cm) USB cord

ORGANIZE, STORE AND CHARGE YOUR SL-B26[®] BATTERY PACKS



NFPA

Charging rack meets requirements of NFPA 1900-11.1.1.2 (2024) mounted in any position

EIGHT-UNIT LI-ION BANK CHARGER

Charge up to eight batteries with Streamlight's lithium-ion battery bank charger. Each charge bay securely holds the battery in place - ideal for mounting on trucks. Low-profile housing (1"; 2.54 cm) requires minimal mounting area.

Charge time = 5.25 hours

Charge indicators over each battery:

- Red = charging
- Green = charged

Charges with or without optional charge cradle. Use the charge cradle for storage as well as to charge your batteries.

BANK CHARGER

SIZE: 10.45" x 4.74" x 1" (26.54 x 12.06 x 2.54 cm)

WEIGHT: 7.6 oz. (216g) w/batteries // 20.88 oz. (592g) w/o batteries

ITEM #	DESCRIPTION
20221	8-Unit Bank Charger - 120V/100V AC
20220	8-Unit Bank Charger - 12V DC
20224	8-Unit Bank Charger - w/ SL-B26 batteries - 120V/100V AC
20223	8-Unit Bank Charger - w/ SL-B26 batteries - 12V DC
44909	120V AC Cord
44923	12V DC Cord



120V AC Charge Cord



12V DC Charge Cord

SURVIVOR PIVOT® USB

The multi-function Survivor Pivot USB provides budget-friendly rechargeability combined with a dual-beam and 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination. It uses an SL-B26® battery pack that is easily interchangeable with alkaline batteries as a backup on-scene. IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested. Class I, Div. 2 safety-rated.



NFPA
Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position


NFPA
Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

SGS
Class I, II, Div. 2, Grps. A, B, C, D, E, F, G; Class III, T-Code: T4 (Pending Approval)

	COMBO		SPOT		FLOOD	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS:	325	80	300	70	300	70
CANDELA:	19,000	5,000	34,000	8,500	300	75
DISTANCE:	267m	141m	369m	184m	35m	17m
RUN TIME [ALK]:	4.5h	12h	5.5h	15h	5.5h	15h
RUN TIME [SL-B26]:	3.75h	13h	4.25h	16h	4.25h	16h

Battery status indicator in switch:

- Green when fully charged
- Red when low voltage
- Flashes red with 15 minutes left on battery



BATTERY: SL-B26 rechargeable battery pack; also accepts (3) AA alkaline
SIZE: 7.93 in. (20.1 cm)
WEIGHT NON-MAGNET: Alkaline - 16.7 oz. (473g) // SL-B26 - 15.8 oz. (448g)
WEIGHT W/MAGNET: Alkaline - 18.1 oz. (513g) // SL-B26 - 17.2 oz. (488g)
COLOR: Orange or Yellow

ORANGE w/o MAGNET	YELLOW w/o MAGNET	ORANGE with MAGNET	YELLOW with MAGNET	DESCRIPTION
91804	91814	91838	91839	Survivor Pivot USB - C1D2

Note: The Survivor Pivot® is not compatible with legacy Survivor® chargers.

SURVIVOR® X USB

The Survivor X USB provides budget-friendly rechargeability combined with added features and increased output. Uses SL-B26® battery pack that is easily interchangeable with alkaline batteries as a backup on-scene. IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested. Lightweight design because we understand that when carrying a lot of gear, every ounce counts. Class I, Div. 2 safety-rated.

	HIGH	LOW
LUMENS:	250	60
CANDELA:	50,000	14,000
DISTANCE:	447m	237m
RUN TIME [SL-B26]:	4h	15h
RUN TIME [ALK]:	5h	15h

FLASH RUNS 8 HOURS



Class I, II, Div. 2, Grps. A, B, C, D, E, F, G; Class III; T-Code: T4

NFPA

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

NFPA

Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

BATTERY: USB rechargeable SL-B26 battery pack; also accepts (3) "AA" alkaline
SIZE: 7.06 in. (17.92 cm)
WEIGHT: Alkaline - 12.8 oz. (363g) // SL-B26 - 11.9 oz. (337g)
COLOR: Orange or Yellow

ORANGE	YELLOW	DESCRIPTION
90044	90244	Survivor X USB - Includes SL-B26 Battery Pack

Note: The Survivor® X is not compatible with legacy Survivor® chargers.

STINGER® 2020

The next evolution in high-performance, work-ready flashlights produces 2,000 lumens. Its aluminum alloy body with textured side panels and an anti-roll design is ergonomically shaped for a sure grip. It features dual power switches and an intuitive mode selector switch for ease of use. Select high for brightest light or low for extended run time.

An SL-B26® USB rechargeable battery pack offers multiple charging options using existing Stinger smart chargers and bank chargers to charge inside the light; use a dual USB cord to charge the battery pack outside the light or a Li-ion battery bank charger to charge multiple batteries at once. IPX7-rated; waterproof to 1m submersion, corrosion-resistant sealed glass lens.

BATTERY: (2) SL-B26 Li-Ion USB rechargeable battery packs
SIZE: 7.67 in. (19.48 cm)
WEIGHT: 12.3 oz. (350g)
COLOR: Black

ITEM #	DESCRIPTION
78101	Stinger 2020 - 120V AC/12V DC
78104	Stinger 2020 - 12V DC
78100	Stinger 2020 - Light Only

TAA COMPLIANT

	HIGH	MEDIUM	LOW
LUMENS:	2,000	850	100
CANDELA:	26,000	12,000	6,000
DISTANCE:	315m	200m	70m
RUN TIME:	2h	4h	24h



Uses two SL-B26® protected Li-Ion USB rechargeable battery packs

SIEGE® X USB

The ultimate rechargeable lantern. This 2-in-1 lantern/flashlight combo provides 360° of light to illuminate a large area as well as a focused beam to light your path. Multiple modes to meet all of your lighting needs plus SOS for emergency signaling. IPX7-rated; waterproof.

Incorporated flashlight produces 300 lumens



BATTERY: (1) SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 4.35 in. (11.05 cm)
WEIGHT: 7.2 oz. (204.12g)
COLOR: Coyote

ITEM #	DESCRIPTION
44956	Seige X USB - Includes SL-B26 battery pack

LANTERN	HIGH	MEDIUM	LOW
LUMENS:	325	170	30
RUN TIME:	4.5h	7.75h	25h

RED	HIGH	SOS
LUMENS:	1.6	1.6
RUN TIME:	22h	90h

FLASHLIGHT	HIGH	LOW
LUMENS:	300	40
CANDELA:	6,000	900
DISTANCE:	155m	60m
RUN TIME:	3.5h	25h



PROTAC® 2L-X USB

	HIGH	LOW
LUMENS:	500	40
CANDELA:	6,800	600
DISTANCE:	165m	49m
RUN TIME [CR123A]:	2.75h	30h
RUN TIME [LI-ION]:	3.75h	30h
STROBE RUNS 3.25 HOURS [CR123A]; 4.5 HOURS [LI-ION]		



TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/high

The ProTac 2L-X features multi-battery versatility - uses two CR123A batteries or one Streamlight protected rechargeable lithium-ion battery. It features a push-button tail switch for momentary or constant on operation, three different user selectable programs and a pocket clip for convenience.

MULTI-FUEL DESIGN:

Runs on SL-B26 battery pack or CR123A batteries



BATTERY: (1) SL-B26 Li-ion USB rechargeable battery pack or (2) CR123A lithium
SIZE: 5.14 in. (13 cm)
WEIGHT: 4.4 oz. (125g) w/SL-B26 // 3.9 oz. (111g) w/CR123A
COLOR: Black

ITEM #	DESCRIPTION
88082	ProTac 2L-X USB - Includes SL-B26 battery pack, Micro-USB cord & holster - Clam
88083	ProTac 2L-X USB - Includes SL-B26 battery pack, Micro-USB cord & holster - Box

PROTAC® HL-X USB

	HIGH	MEDIUM	LOW
LUMENS:	1,000	400	65
CANDELA:	27,100	10,000	1,600
DISTANCE:	330m	200m	80m
RUN TIME [CR123A]:	1.25h	3h	20h
RUN TIME [LI-ION]:	1.25h	3h	20h
STROBE RUNS 2.5 HOURS [CR123A]; 3.25 HOURS [LI-ION]			



TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/med/high



The ProTac HL-X features multi-battery versatility - uses two CR123A batteries or one Streamlight protected rechargeable lithium-ion battery. It features a push-button tail switch for momentary or constant on operation, three different user selectable programs and a pocket clip for convenience.

MULTI-FUEL DESIGN:

Runs on SL-B26 battery pack or CR123A batteries



BATTERY: (1) SL-B26 Li-ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 5.43 in. (13.8 cm)
WEIGHT: 6.2 oz. (176g) w/SL-B26 // 5.7 oz. (162g) w/CR123A
COLOR: Black

ITEM #	DESCRIPTION
88084	ProTac HL-X USB - Includes SL-B26 battery pack, Micro-USB cord & holster - Clam
88085	ProTac HL-X USB - Includes SL-B26 battery pack, Micro-USB cord & holster - Box

PROTAC® 90X USB

The MULTI-FUEL ProTac 90X is an EDC light with a twist. It features a right-angle head that gives extra lighting capability for those with multiple lighting needs. Carry in your hand or attach to your MOLLE, belts, harnesses and other gear for hands-free use.

BATTERY: (1) SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium
SIZE: 4.39 in. (11.1 cm)
WEIGHT: 4.9 oz. (139g) w/SL-B26 // 4.4 oz. (125g) w/CR123A
COLOR: Black



TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/medium/high

	HIGH	MEDIUM	LOW
LUMENS:	1,000	300	65
CANDELA:	7,350	2,060	450
DISTANCE:	171m	91m	42m
RUN TIME (CR123A):	2.5h	4h	21h
RUN TIME (SL-B26):	1.75h	4.75h	24h

STROBE RUNS 2.5 HOURS (CR123A); 3.5 HOURS (SL-B26)

ITEM #	DESCRIPTION
88095	ProTac 90X USB - Includes SL-B26 Battery pack & holster

PROTAC HL® 5-X USB

The ProTac HL 5-X features MULTI-FUEL innovation that provides you the versatility to use four CR123A batteries or two Streamlight SL-B26® protected Li-Ion USB rechargeable battery packs. Multiple battery sources can help reduce down time and keep you powered up. IPX7-rated; waterproof to 1m for 30 minutes.



BATTERY: (2) SL-B26 Li-Ion USB rechargeable battery packs
SIZE: 9.53 in. (23.65 cm)
WEIGHT: 1 lb. 3.4 oz. (550g)
COLOR: Black



MULTI-FUEL DESIGN:
 Runs on SL-B26 battery pack or CR123A batteries

TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/med/high

CR123A	HIGH	MEDIUM	LOW
LUMENS:	2,500	1,000	250
CANDELA:	37,000	14,100	3,620
DISTANCE:	385m	237m	120m
RUN TIME (CR123A):	1.5h	2.5h	10.5h

STROBE RUNS 1.5 HOURS (CR123A)

SL-B26	HIGH	MEDIUM	LOW
LUMENS:	3,500	1,000	250
CANDELA:	51,000	14,100	3,620
DISTANCE:	452m	237m	120m
RUN TIME (SL-B26):	1.25h	2.5h	10.5h

STROBE RUNS 1.25 HOURS (SL-B26)

ITEM #	DESCRIPTION
88080	ProTac HL 5-X USB - Includes (2) SL-B26 battery packs, Micro-USB cord & lanyard - Clam
88081	ProTac HL 5-X USB - Includes (2) SL-B26 battery packs, Micro-USB cord & lanyard - Box

POLYTAC 90® X USB

Flexible, rugged and super bright, the PolyTac 90 X USB is a rechargeable system that includes a Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack. Built with the rigors of the job in mind, it has a durable, waterproof construction. Its power button with a built in battery life indicator will let you know when it is time to recharge your battery giving you the confidence to stay focused on the task at hand.

BATTERY: (1) SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 4.43 in. (11.25 cm)
WEIGHT: 4.8 oz. (136g) w/SL-B26 // 4.3 oz. (122g) w/CR123A
COLOR: Orange, Yellow or Black

ORANGE	YELLOW	BLACK	DESCRIPTION
88838	88836	88835	PolyTac 90 X USB - Includes SL-B26 battery pack
88837	--	--	PolyTac 90 X USB - Includes SL-B26 battery pack & gear keeper



	HIGH	LOW
LUMENS:	500	85
CANDELA:	7,000	1,050
DISTANCE:	167m	64m
RUN TIME (CR123A):	2.5h	12h
RUN TIME (SL-B26):	3.75h	19h

Gear Keeper® Tether features spectra nylon line with 36" extension and 6 oz. retraction force.



NFPA Meets requirements of NFPA 1971-8.6 (2018)

POLYTAC® X USB

Multi-Fuel Design provides you the versatility to use two CR123A batteries or one Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack. Superior grip texture provides a comfortable/slip-resistant feel. IPX7-rated; waterproof to 1m for 30 minutes.

	HIGH	MEDIUM	LOW
LUMENS:	600	260	35
CANDELA:	11,485	4,930	675
DISTANCE:	205m	135m	50m
RUN TIME (CR123A):	2.75h	5.5h	34h
RUN TIME (SL-B26):	3.5h	5.75h	36h

STROBE RUNS 8 HOURS

MULTI-FUEL DESIGN: Runs on SL-B26 battery pack or CR123A batteries



TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/medium/high

BATTERY: (1) SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 5.46 in. (13.87 cm)
WEIGHT: 4.9 oz. (139g) w/SL-B26 // 4.4 oz. (125g) w/CR123A
COLOR: Coyote, Yellow or Black

CLAM	BOX	DESCRIPTION
88610	88613	PolyTac X USB - Includes SL-B26 battery pack & USB Cord - Black
88611	88614	PolyTac X USB - Includes SL-B26 battery pack & USB Cord - Yellow
88612	88615	PolyTac X USB - Includes SL-B26 battery pack & USB Cord - Coyote

VANTAGE® 180 X USB

This light is the most versatile rechargeable firefighter's light. It a helmet mounted light, right angle light and a hand-held flashlight. It is a rechargeable system that includes a Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack with integrated USB port. IPX7-rated; waterproof.

	HIGH	LOW
LUMENS:	250	100
CANDELA:	7,200	2,650
DISTANCE:	170m	103m
RUN TIME (CR123A):	4h	12h
RUN TIME (SL-B26):	5h	15h

Head articulates 180° to aim the beam.

MULTI-FUEL DESIGN: Runs on SL-B26 battery pack or CR123A batteries



Rear LED Taillight changes from blue to white:

- Blue LED for helmet mount use and visibility in heavy smoke
- White LED for a downcast flood light to see what's at your feet; switches from blue when head is at a 90° angle



NFPA Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

BATTERY: (1) SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 5.2 in. (13.2 cm)
WEIGHT: 5.9 oz. (167g) w/SL-B26 // 5.5 oz. (156g) w/CR123A
COLOR: Orange or Black

ORANGE	BLACK	DESCRIPTION
88911	88913	Vantage 180 X USB - Includes SL-B26 battery pack

PROTAC® RAIL MOUNT HL-X PRO

[(STROBE)]
Double tap
switch to activate

	HIGH	LOW
LUMENS:	1,000	60
CANDELA:	50,000	3,100
DISTANCE:	447m	111m
RUN TIME [CR123A]:	1.25h	21h
RUN TIME [SL-B26]:	1.75h	24h
STROBE RUNS 2.5 HOURS [CR123A] 3.5 HOURS [SL-B26]		

TEN-TAP® Programmable switch allows user selection of one of three different programs:

- high/strobe (factory default)
- high only
- low/high



The ProTac series expands its weapon-mounted lights with this 50,000 candela light with a 447m beam distance. It features a fixed-mount for MIL-STD 1913 or M-LOK® compatible rails. Lightweight, this bright light can be used in close quarter combat or to identify medium range threats. Rugged, reliable and features a remote switch with momentary/constant on operation or a standard push-button tail switch. IP67-rated with the Standard button switch installed; waterproof to 1 meter for 30 minutes. IPX4-rated with the remote pressure switch installed.

BATTERY: (2) CR123A lithium or (1) SL-B26 USB rechargeable battery pack
SIZE: 5.43 in. (13.79 cm)
WEIGHT: 7.2 oz. (204.1g) w/SL-B26 // 6.6 oz. (187.1g w/CR123A)
COLOR: Black

MULTI-FUEL DESIGN:
Runs on CR123A or SL-B26 batteries



Jack Cap® tail switch provides momentary and "constant on" operation



ITEM #	DESCRIPTION
88127	ProTac Rail Mount HL-X Pro USB - Includes Jack-Cap®, M-LOK® Kit, Momentary Switch, Hardware Kit, 2.5 mm Allen Wrench, (1) SL-B26 USB Battery, 40" (101.6 cm) USB Cord - Box
88129	ProTac Rail Mount HL-X Pro USB - Light Only - Includes Jack-Cap®, M-LOK® Kit, 2.5 mm Allen Wrench, (1) SL-B26 USB Battery, 40" (101.6 cm) USB Cord - Box

PROTAC® RAIL MOUNT HL-X USB LONG GUN LIGHT

[(STROBE)]
Double tap
switch to activate

	HIGH	LOW
LUMENS:	1,000	60
CANDELA:	50,000	3,100
DISTANCE:	442m	110m
RUN TIME [CR123A]:	1.25h	20h
RUN TIME [SL-B26]:	1.5h	23h
STROBE RUNS 2.5 HOURS [CR123A]; 3.25 HOURS [SL-B26]		

The ProTac series expands its weapon-mounted lights with this 1,000 lumen light featuring a fixed-mount for MIL-STD-1913 or M-LOK® compatible rails. Lightweight, this bright light can be used in close quarter combat or to identify medium range threats. Rugged, reliable and features a remote switch with momentary or "constant on" operation or a standard push-button tail switch. IP67-rated with the standard button switch installed; waterproof to 1 meter for 30 minutes. IP54-rated with the remote pressure switch installed.

BATTERY: (2) CR123A lithium or (1) SL-B26 Li-Ion USB rechargeable battery pack
SIZE: 5.43 in (13.8 cm)
WEIGHT: 6.9 oz. (195.6g) w/SL-B26 // 6.4 oz. (181.4g) w/CR123A
COLOR: Black



MULTI-FUEL DESIGN:
Runs on CR123A or SL-B26 battery pack

TEN-TAP® Programmable switch allows user selection of one of three different programs:

- high/strobe (factory default)
- high only
- low/high

ITEM #	DESCRIPTION
88071	ProTac Rail Mount HL-X USB - Includes remote pressure switch, tailcap switch, mounting hardware and M-LOK mount

THESE PRODUCTS ALSO ACCEPT SL-B26 BATTERY PACKS

[NOT AVAILABLE AS SYSTEMS]

PROTAC HL® USB HEADLAMP

This is the perfect rechargeable headlamp for when your task requires both hands and a bright light with a wide, long-range beam. 90° tilting head reduces neck fatigue. TEN-TAP® Programming lets you choose from three operating modes. IPX4-rated; water-resistant; 1m impact-resistance tested. Multi-fuel capability: includes rechargeable lithium-ion battery; also a or protected lithium-ion USB rechargeable battery.

ITEM #	DESCRIPTION
61305	ProTac HL USB Headlamp
61306	ProTac HL USB Headlamp- 120V AC/12V DC

	HIGH	MEDIUM	LOW
LUMENS:	1,000	400	65
CANDELA:	13,500	5,400	900
DISTANCE:	232m	147m	60m
RUN TIME:	1.75h	3.5h	24h

HL®



1000
LUMENS

BATTERY: Lithium-ion, SL-B26 Li-Ion USB rechargeable battery pack
WEIGHT: 8.1 oz. (230g)
COLOR: Black

PROTAC HL® USB

Delivers extraordinary brightness within a wide beam so you can see into those dark corners. Ideal for areas where you need a lot of light to see all around you. Uses rechargeable lithium-ion battery; also accepts two CR123A lithium batteries or a Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack.

BATTERY: Lithium-ion, SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 6.5 in. (16.5 cm)
WEIGHT: 7.2 oz. (204g)
COLOR: Black

ITEM #	DESCRIPTION
88052	ProTac HL USB - Includes Micro-USB cord & holster - Clam
88054	ProTac HL USB - 120V AC/12V DC and holster - Clam

	HIGH	MEDIUM	LOW
LUMENS:	1,000	400	65
CANDELA:	35,000	4,100	700
DISTANCE:	219m	133m	53m
RUN TIME:	1.5h	3.5h	23h

STROBE RUNS 1.5 HOURS

HL®



1000
LUMENS

TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/medium/high

MULTI-FUEL DESIGN:
Runs on lithium-ion battery, SL-B26 battery pack or CR123A batteries

PROTAC® HPL USB

High performance, high lumen tactical light - it's USB rechargeable, so you can charge on-the-go using almost any USB source. It accepts multiple battery types including a rechargeable lithium-ion battery, Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack or two CR123A lithium batteries so you'll always have power when you need it - reduces down time.

BATTERY: Lithium-ion, SL-B26 Li-Ion USB rechargeable battery pack or (2) CR123A lithium batteries
SIZE: 7.08 in. (18 cm)
WEIGHT: 9.24 oz. (262g)
COLOR: Black

ITEM #	DESCRIPTION
88076	ProTac HPL USB - Includes Micro-USB cord & holster - Clam
88078	ProTac HPL USB - 120V AC/12V DC and holster - Clam

	HIGH	MEDIUM	LOW
LUMENS:	1,000	400	65
CANDELA:	35,000	14,100	2,250
DISTANCE:	374m	237m	95m
RUN TIME:	1.5h	3h	20h

STROBE RUNS 3 HOURS

HL®



1000
LUMENS

TEN-TAP® Programmable - choose from three programs:

- high/strobe/low
- high only
- low/medium/high

MULTI-FUEL DESIGN:
Runs on lithium-ion battery, SL-B26 battery pack or CR123A batteries



STREAMLIGHT®

Streamlight, Inc.
30 Eagleville Road
Eagleville, PA U.S.A 19403
streamlight.com

(800) 523-7488 Toll-Free
(800) 220-7007 Fax
(610) 631-0600
(610) 631-0712 Fax

©2024 Streamlight, Inc. 4/24 ISO 9001:2008 certified 991074 asi/89871

All rights reserved. Trademarks of companies mentioned herein appear for identification purposes only and are the property of their respective companies.