

The Stinger LED HL is a high lumen flashlight that provides 800 lumens of maximum illumination. Its wide beam pattern gives you a bright flood light that will light up the area around you.

Multi-function push-button switch lets you choose high, medium, low and strobe modes

NiMH battery rechargeable up to 1000 times; also accepts NiCd battery

Anodized aluminum construction with non-slip rubberized comfort grip

Access any of the 3 lighting modes via the tailcap or the head-mounted switch on the DS model. Switches operate independently and are designed for extremely long life



**800 LUMENS!**

**HL®**

3 lighting modes and strobe:

- High for maximum illumination: 800 lumens; 24,000 candela; 310m beam; runs 1.5 hours
- Medium for intense brightness and longer run time: 400 lumens; 12,000 candela; 219m beam; 2.5 hours
- Low for extended run time: 200 lumens; 6,000 candela; 155m beam; runs 5 hours
- Strobe for signaling or disorienting: runs 3 hours

Optimized electronics provide regulated intensity throughout battery charge

Deep-dish parabolic reflector produces a concentrated beam with optimum peripheral illumination

IPX4 water resistant  
1 meter impact resistance tested

Serialized for positive identification

Stinger LED HL: 8.41" (21.36 cm); 12.4 oz (352 g)  
Stinger DS LED HL: 8.85" (22.48 cm); 12.8 oz (364 g)

Limited Lifetime Warranty  
Visit [www.streamlight.com](http://www.streamlight.com) for full warranty information

See reverse for system configurations

Item #	Item Description
<b>Stinger LED HL</b>	
75440	Stinger LED HL - IEC Type C (230V) AC/12V DC – 2 holders (NiMH)
75448	Stinger LED HL - IEC Type G (240V) AC/12V DC – 2 holders (NiMH)
75430	Stinger LED HL - IEC Type A (120V) AC/12V DC – 2 holders Smart Charge (NiMH)
75435	Stinger LED HL - IEC Type A (100V) AC/12V DC – 2 holders (NiMH)
75442	Stinger LED HL - IEC Type C (230V) AC (NiMH)
75449	Stinger LED HL - IEC Type G (240V) AC (NiMH)
75431	Stinger LED HL - IEC Type A (120V) AC Smart Charge (NiMH)
75436	Stinger LED HL - IEC Type A (100V) AC (NiMH)
75432	Stinger LED HL - 12V DC (NiMH)
75434	Stinger LED HL - IEC Type A (120V) AC/12V DC PiggyBack Smart Charge (NiMH)
75699	Stinger LED HL - IEC Type A (120V) AC/12V DC PiggyBack Smart Charge Kryptek (NiMH)
75429	Stinger LED HL - (WITHOUT CHARGER) (NiMH)
75698	Stinger LED HL - (WITHOUT CHARGER) Kryptek (NiMH)
<b>Stinger DS LED HL®</b>	
75464	Stinger DS LED HL - IEC Type C (230V) AC/12V DC – 2 holders (NiMH)
75472	Stinger DS LED HL - IEC Type G (240V) AC/12V DC – 2 holders (NiMH)
75454	Stinger DS LED HL - IEC Type A (120V) AC/12V DC Smart Charge – 2 holders (NiMH)
75459	Stinger DS LED HL - IEC Type A (100V) AC/12V DC – 2 holders (NiMH)
75466	Stinger DS LED HL - IEC Type C (230V) AC (NiMH)
75473	Stinger DS LED HL - IEC Type G (240V) AC (NiMH)
75455	Stinger DS LED HL - IEC Type A (120V) AC Smart Charge (NiMH)
75460	Stinger DS LED HL - IEC Type A (100V) AC (NiMH)
75456	Stinger DS LED HL - 12V DC Smart Charge (NiMH)
75458	Stinger DS LED HL - IEC Type A (120V) AC/12V DC Smart Charge PiggyBack (NiMH)
75453	Stinger DS LED HL - (WITHOUT CHARGER) (NiMH)

