

**Lightweight ATEX-rated rechargeable lantern weighs just 875 grams.
 It produces a tight beam that is optimal for firefighting operations.**



<p>High, low and blink modes:</p> <ul style="list-style-type: none"> - High for a bright, far-reaching beam: 180 lumens; 100,000 candela; 632m beam; runs 3.5 hours - Low for a less intense beam and longer run time: 70 lumens; 40,000 candela; 400m beam; runs 7.5 hours - Blink for signaling: runs 5.5 hours 	<p>ATEX: II 3G Ex ic nA IIC T5 Gc II 3D Ex tc IIIC T54°C Dc FTZU 08 ATEX 0139X IECEx: Ex ic nA IIC T5 Gc Ex tc IIIC T54°C Dc IECEx FTZU 15.0038X InMetro: Ex nA ic IIC T5 Gc Ex tc IIIC T54°C Dc IP66 DNV 16.0076X Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position</p>
<ul style="list-style-type: none"> - Deep-dish parabolic reflector produces a tight beam with optimum peripheral illumination to aid in navigation - Optimized electronics provide regulated intensity 	<p>Limited Lifetime Warranty Visit streamlight.com for full warranty information</p> <p>#44753 - Vulcan LED ATEX Standard System - 230V AC/12V DC - Orange #44758 - Vulcan LED Standard System - 230V AC/12V DC - Orange - InMetro #44752 - Vulcan LED ATEX Standard System - 240V AC/12V DC - Orange #44754 - Vulcan LED ATEX Standard System - 100V/120V AC/12V DC - Orange #44751 - Vulcan LED ATEX Vehicle Mount System - 12V DC - Orange #44756 - Vulcan LED Vehicle Mount System - 12V DC - Orange - InMetro #44750 - Vulcan LED ATEX Light Only - Orange #44755 - Vulcan LED Light Only - Orange - InMetro</p>
<p>IP66-rated; dust tight and water-resistant; 2m impact resistance tested</p>	
<p>19.76 cm (7.7 in.); 875 grams (1.93 lbs.)</p>	