

PRODUCT FACT SHEET

ARGO[®] LED HEADLAMP ALKALINE AAA BATTERY-POWERED HEADLAMP

MARKET	
APPLICATIONS:	Outdoor, Sporting Goods, Automotive, Hardware/Do-It-Yourself, Industrial, Emergency Medical Services, Safety, Gift, Consumer, Pest Control, Boating
DESCRIPTION:	The Argo® headlamp with adjustable elastic head strap features a single C4® power LED for long distance lighting with three output modes and a low battery warning indicator.
CASE MATERIAL:	Tough ABS thermoplastic construction with elastomer over mold. Available in Yellow
DIMENSIONS:	Face Cap Diameter: 1.75 in. (4.45cm) Maximum Depth (including head strap mounting plate): 2.40 in. (6.09 cm)
WEIGHT:	5.40 oz (153 grams) with batteries (included with purchase).
LENS:	Unbreakable polycarbonate lens.
LIGHT SOURCE:	One (1) White C4 $^{\odot}$ LED technology, impervious to shock with a 50,000 hour lifetime.
LIGHT OUTPUT:	High - 150 Lumens, 9250 candela peak beam intensity, and 190 meter beam distance. Medium - 100 lumens, 6375 candela peak beam intensity, and 160 meter beam distance. Low - 45 lumens, 2750 candela peak beam intensity, and 103 meter beam distance.
ON/OFF:	Push-button sequence through modes, High, Medium, Low and Off
RUN TIME:	See chart. All claims to 10% of initial lumen output.
BATTERY:	Three (3) "AAA" size, Alkaline batteries.
FEATURES:	 C4[®] LED technology for extreme brightness. Low Battery Indicator - Red LED flashes when battery voltage is low and batteries are near the end of their usable life. LED is located in the reflector in between the "Low Batt" marking and functions while the light is energized. IPX4 rated for water resistant operation. 2 meter impact resistance tested. 90 degree tilting head. Rubber Hard Hat Strap (included in purchase).
WARRANTY:	Streamlight's Limited Lifetime Warranty
APPROVALS:	Class 1, Division 2, Groups A,B,C,D; Class II, Division 2, Groups F,G; Class III, Temp Code: T5
	CEMeets applicable European Community directives.
OPTIONAL ACCESSORIES:	N/A PERFORMANCE CURVE
	FL1 STANDARD HIGH MEDIUM LOW 150.0
OUTPUT	150 100 45 LUMENS LUMENS LUMENS
RUNTIME	Image: Weight of the second
DICTANCE	

DISTANCE INTENSITY

All performance claims tested to ANSI/PLATO FL1-2016 Standard Issued: 10/01/2004 Revised: 04/07/2017 Rev: 8

190m

9250cd

160m

6375cd

103m

2750cd

1

Hours

2