

ProTac HL® HEADLAMP HIGH LUMEN LITHIUM HEADLAMP

MARKET
APPLICATIONS: Sporting Goods, Consumer, Industrial, Law Enforcement, Security, Emergency Medical Services, Hardware/Tool

DESCRIPTION:

With 635 lumens of blinding light, the ProTac HL® Headlamp is the brightest addition to the headlamp series. The ProTac HL® Headlamp offers the latest in power LED technology and three different user selectable programs. The combination of small size and output from the C4® LED result in one of the brightest headlights for its' size. Packaged with an elastic headband and a rubber headband for helmet mounting.

CASE MATERIAL:

6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS:

 Facecap Diameter: 1.20 in. (3.05 cm) Width: 3.66 in. (2.54 cm)
 Maximum Depth (including headband mounting plate): 2.60 in. (6.60 cm)

WEIGHT:

6.6 oz (187 grams) with batteries (included with purchase).

LENS:

Glass lens, gasket sealed.

LIGHT SOURCE:

C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT:

See chart. Optimized electronics provides regulated intensity.


ON/OFF:

Multi-function, push-button switch. One handed operation of momentary or variable intensity. TEN-TAP® programmable switch allows user selection of one of three different programs: high/medium/low (factory default), high only, or low/medium/high.

RUN TIME:


See chart. All claims to 10% of initial lumen output.

BATTERY:

Two (2) 3 Volt CR123A Lithium batteries. CR123A batteries have a shelf life of 10 years.

FEATURES:


C4® LED technology for extreme brightness.

IPX4 rated for water resistant operation. All openings o-ring sealed.

1 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life.


TEN-TAP® programmable switch allows user to select one of three different programs.

Serialized for positive identification.





WARRANTY:

Streamlight's Limited Lifetime Warranty

APPROVALS:

 Meets applicable European Community directives. 
OPTIONAL
ACCESSORIES:

N/A

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		635 LUMENS	105 LUMENS	20 LUMENS
RUNTIME		1h 45min	8h	36h
DISTANCE		184m	76m	33m
INTENSITY		8,500 cd	1,450 cd	280 cd

