

PORTABLE SCENE LIGHT // PORTABLE SCENE LIGHT EXT
RECHARGEABLE, HIGH-LUMEN FLOOD LIGHT

DESCRIPTION: The Portable Scene Light is an industrial-duty, rechargeable, completely portable, high-lumen flood light that can be fully deployed in less than 30 seconds. It uses (12) LEDs and wide pattern reflectors to produce a uniform flood pattern and (3) light output intensities. Its telescoping pole and rotating head extend to an overall height of 72 inches or 84 inches for the EXT version. Onboard stabilizing legs can be deployed for high wind or uneven terrain. System ships with a heavy-duty shoulder strap, AC charger, and 12VDC cord. Ideal for field maintenance, inspection of construction sites and remote equipment, military operations, and general scene lighting.

CASE MATERIAL: High-impact thermoplastic housing, sealed. Available in Yellow.

DIMENSIONS: Body Width: 6.5 in. (16.5 cm) Overall Height: 11 in. (27.9 cm) Head Diameter: 6.7 in. (17 cm)
(RETRACTED POSITION) Portable Scene Light - Length: 22.5 in. (57.2 cm)
 Portable Scene Light EXT - Length: 25.5 in. (64.8 cm)

WEIGHT: Portable Scene Light: 25.8 lbs (11.7 kg)
 Portable Scene Light EXT: 26.3 lbs (11.9 kg)

LENS: Unbreakable polycarbonate with scratch-resistant coating. O-ring sealed.

LIGHT SOURCE: (12) high-power white LEDs, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT: See chart. (12) wide pattern parabolic reflectors produce a smooth pattern. Optimized electronics provide fully regulated intensity; (3) selectable light output intensities.

ON / OFF: Toggle switch allows for operation from internal battery or continuous operation from external 12VDC or AC power source. Memory feature saves the last used light output setting when powered on.

RUN TIME: See chart for battery operated run times. All run time claims to 10% output level. Battery status indicator illuminates red when battery is low. All models include AC power supply and 10 ft. 12VDC power cord for continuous operation while simultaneously charging batteries.

BATTERY: Zero-maintenance 12V, 14.0Ah sealed lead acid battery, rechargeable up to 500 times. Red and green LED charge status indicators. 10-hour charge to 90% battery capacity with continuous trickle charge to maximize battery capacity. Battery will continue to charge while operating directly from an external power source when using the 12VDC cord or AC charger.

FEATURES: LED technology and circuit to provide regulated light output throughout battery life. IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes. Designed to resist 40 mph wind continuous in all directions with head fully extended. Serialized for positive identification.

APPROVALS:  IP67 tested

 CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL ACCESSORIES: 100VAC, 230VAC, or 240VAC power cords. 12VDC (automobile) charge cord. Quick release shoulder/waist strap.

	HIGH	MEDIUM	LOW
LUMENS	10,000	5,300	2,000
RUN TIME	2h	4h	12h
DISTANCE	616m	445m	300m
CANDELA	95,000	49,500	22,450