

DOUBLE CLUTCH® USB HEADLAMP

DESCRIPTION: Compact, lightweight, high-performance USB-rechargeable LED headlamp. The Double Clutch® USB offers multi-fuel technology and one-handed “glove-friendly” facecap rotation to operate the light. The headlamp additionally offers spot or flood beams and high or low lighting modes. The lithium polymer battery charges inside or outside of the headlamp or three AAA batteries can be used for disposable power. The Double Clutch USB headlamp has been specifically engineered to maximize run time and minimize weight with a low-profile design and an optimized center of gravity providing maximum comfort and stability during use. The headlamp is packaged with an elastic head strap and rubber helmet strap. Rechargeable and alkaline models available.

CASE MATERIAL: Engineering polymer; available in yellow or black.

DIMENSIONS: Facecap Diameter: 1.75 in (4.44 cm) Width: 2.50 in (6.35 cm)
Depth (including head strap plate): 1.66 in (4.22 cm)

WEIGHT: 3.7 oz (105 g) with elastic head strap and lithium polymer battery
4.2 oz (119 g) with elastic head strap and three (3) AAA alkaline batteries

LENS: Unbreakable polycarbonate lens, sealed

LIGHT SOURCE: LED technology, impervious to shock with a 50,000-hour lifetime

LIGHT OUTPUT: **High:** 125 lumens, 1,700 candela peak beam intensity, 82 m beam distance
Low: 30 lumens, 400 candela peak beam intensity, 40 m beam distance




ON/OFF: Facecap at center position for “off.” Rotate 90° for “on” (spot or flood based on rotation direction). Double tap for intensity change; previous intensity stored in memory.

RUN TIME: See charts for battery type. All claims to 10% of initial lumen output.

BATTERY*: Rechargeable lithium polymer pack; fully recharges in 4 hours
Three (3) AAA batteries (alkaline or lithium)

FEATURES: LED technology for extreme brightness
Multi-fuel technology; lithium polymer USB charging or AAA batteries
Facecap rotation operates light; can be operated using heavy gloves
Spot and flood beams
High or low lighting modes with previous mode memory
IPX4-rated design; water-resistant
2-meter impact resistance tested
60-degree tilting head















APPROVALS:  Meets applicable United Kingdom and European Community Directives

 CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL ACCESSORIES: AC/USB power adapters

	Lithium Polymer			AAA Alkaline		
	FL1 STANDARD	HIGH	LOW	FL1 STANDARD	HIGH	LOW
OUTPUT		125 LUMENS	30 LUMENS		125 LUMENS	30 LUMENS
RUN TIME		3h 30min	10h		6h	18h
SPOT DISTANCE		82m	40m		82m	40m
SPOT INTENSITY		1,700cd	400cd		1,700cd	400cd
FLOOD DISTANCE		31m	4m		31m	4m
FLOOD INTENSITY		250cd	70cd		250cd	70cd

