



# PRODUCT FACT SHEET

## Pro Tac HL® USB

### DUAL FUEL - LITHIUM ION RECHARGEABLE or 2X CR123 FLASHLIGHT

**MARKET**

**APPLICATIONS:** Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive, Sporting Goods, Consumer.

**DESCRIPTION:**

The Pro Tac HL® USB is a versatile tactical light that can charge from multiple sources and use three battery types; Streamlight's P/N 74175 rechargeable lithium ion battery, two CR123A batteries, or proprietary Streamlight® Li-Ion USB rechargeable battery pack. (see Battery detail below). This light will charge from a laptop or most USB wall chargers. Multi battery versatility means you can always use primary disposable cells to power the light when a charging source is not available. Designed for use in all markets, it features a tail cap switch for momentary or constant on operation, three different user selectable programs and a pocket clip for convenience. The aluminum housing with Type II Military Spec anodizing helps make the light extremely durable and abrasion resistant. Packaged with a removable pocket clip and holster. Available in Black.

**CASE MATERIAL:** 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in Black.

**DIMENSIONS:** Length: 6.50 in. (16.5 cm) Head Diameter: 1.23 in. (3.1 cm) Body Diameter: 1.07 in. (2.7 cm)

**WEIGHT:** 7.2 oz (204 grams) with Li Ion rechargeable battery. (included in purchase)

**LENS:** Glass lens; gasket sealed.

**LIGHT SOURCE:** LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See chart. Fully regulated output for consistent lumen performance over the battery life.

**ON/OFF:** Multi-function, push-button tactical tail switch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/medium/high.

**RUN TIME:** See Chart. All runtime claims are to 10% of initial lumen output. Strobe: 1.5 continuous hours.

**BATTERY:** Streamlight Lithium Ion cell pack (P/N 74175) with on board safety circuit. Rechargeable up to 1000 times. The light will also function if you install two 3V CR123A lithium cells, or a Streamlight® SL-B26™ protected Li-Ion USB rechargeable battery pack with on-board safety control, 2600mAh, rechargeable up to 500 times. Recharges in 5 hours. (Note - SL-B26™ cell will not charge in the light.)

**CHARGING:** Digital control circuit that prevents overcharge. Charge indication LED: Red - Charging; Green - Charged. Fully recharges battery in 7 hours with Streamlight AC/USB adaptor and charges the 74175 Rechargeable Lithium Ion battery in the product.

**FEATURES:**



LED technology for extreme brightness.  
 IPX4 rated for water resistant operation. All openings o-ring sealed.  
 1 meter impact resistance tested.  
 LED Solid State Power Regulation provides maximum light output throughout battery life.  
 TEN-TAP® programmable switch allows user to select one of three different programs.  
 Anti-roll face cap.  
 Serialized for positive identification.  
 Micro USB charge port under water resistant sliding cover. Rechargeable using supplied USB cord.  
 Removable pocket clip and Holster

**APPROVALS:** CE Meets applicable European Community Directives.  
 BC CEC Compliant

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL ACCESSORIES:** AC/USB adaptor(s), 12V DC USB Auto adaptor, and Safety Wands

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		1000 LUMENS	380 LUMENS	65 LUMENS
RUNTIME		1h 30min	3h 30min	23h
DISTANCE		219m	133m	53m
INTENSITY		12,000cd	4,420cd	700cd

