

WAYPOINT® 400 LITHIUM-ION RECHARGEABLE HIGH-PERFORMANCE PISTOL-GRIP SPOTLIGHT

DESCRIPTION:	Handheld & powerful, the Waypoint® 400 rechargeable spotlight offers high, medium, and low intensity modes, and the latest in power LED technology. The spotlight provides portability and long run times using a rechargeable lithium-ion battery, making it the perfect choice for a variety of applications. Its weight-balanced design virtually eliminates hand fatigue, and the light will float if dropped into water for easy retrieval.				
CASE MATERIAL:	High-impact polycarbonate housing. Rubberized lens ring and cushioned-grip handle. Available in yellow and black.				
DIMENSIONS:	Length: 6.75 in (17.15 cm) Height: 7.14 in (18.14 cm) Head Diameter: 3.62 in (9.20 cm)				
WEIGHT:	1.52 lbs (691 g)				
LENS:	Unbreakable polycarbonate lens, O-ring sealed.				
LIGHT SOURCE:	High-power LED, impervious to shock with a 50,000-hour lifetime				
	High, Medium, and Low output. See chart. Deep-dish parabolic reflector produces a long-range targeting beam with optimum peripheral illumination. Optimized electronics provides regulated intensity.				
ON/OFF:	Trigger style switch with momentary or click on/off operation. Secondary rotary switch selects output mode.				
	See chart. All claims to 10% of initial lumen output.				
BATTERY:	Lithium-ion with on-board safety control circuit, rechargeable up to 800 times				
CHARGING:	Digital control circuit prevents overcharge. Use only Streamlight supplied charger. Fully recharges battery in 4 hours and charges battery in product. Charge LED indication: Red - Charging; Green - Charged				
	High-power LED for extreme brightness LED Solid State Power Regulation provides maximum light output throughout battery life IPX8-rated design; waterproof to 2 meters 1-meter impact resistance tested Light floats if dropped into water Integrated stand for hands-free scene lighting Removable lanyard				
WARRANTY:	Streamlight's Limited Lifetime Warranty				
APPROVALS:	CE K Meets applicable United Kingdom and European Community Directives ⓒ CEC Compliant				
OPTIONAL ACCESSORIES:	Red and green filters				

ACCESSORIES:

OU RUN DIS INT

Red and green filters

	FL1 STANDARD	HIGH	MEDIUM	LOW
ITPUT	342	1400 Lumens	600 lumens	38 Lumens
N TIME	\bigcirc	3h 15min	7h 30min	84h
TANCE	Ν	1,265m	812 m	200 m
TENSITY		400,000 cd	165,000 cd	10,000cd

All performance claims to ANSI/PLATO FL1-2019 Standard