

E-SPOT® LITEBOX[®] // E-SPOT® FIREBOX®

RECHARGEABLE LED LANTERN

DESCRIPTION:	The E-Spot [®] LiteBox [®] and FireBox [®] deliver 1,500 lumens and 110,000 candela of focused light. The lithium-ion battery provides enhanced performance in a lightweight device. The large tactile push-button switch (with built-in battery status indicator) and a large grip area make this lantern easy to use, even with gloved hands. This light is also easy to carry, whether it's by hand or with the heavy-duty shoulder strap. The articulating head and ability to stand the light upright allows the user to aim light right where it's needed. The E-Spot [®] models use four (4) LEDs with deep parabolic reflectors for a long-range, focused beam pattern. The LiteBox [®] is also available in a Power Failure version.			
CASE MATERIAL:	High-impact ABS thermoplastic.			
DIMENSIONS:	Length: 11.2 in (28.4 cm) Width: 5.0 in (12.7 cm) Height: 6.4 in (16.3 cm)			
WEIGHT:	3.1 lbs. (1389 g)			
LENS:	Unbreakable polycarbonate with scratch-resistant coating.			
LIGHT SOURCE:	Four (4) high-power LEDs, impervious to shock with a 50,000-hour lifetime. Two (2) ultra-bright blue taillight LEDs (FireBox® models only).			
LIGHT OUTPUT:	See chart. Optimized electronics provide regulated intensity.			
ON/OFF:	Push-button with integrated battery charge indicator. Press and hold to cycle through the different modes.			
RUN TIME:	See chart.			
BATTERY:	Lithium-ion 7.2V, 6800 mAh with onboard safety control, rechargeable up to 500 times. Recharges in 7 hours with provided power supplies. Red and green LEDs in the push-button indicate battery status. When operating, flashing red indicates charging is needed. When charging, green indicates fully charged.			
	Cool white LED technology for extreme brightness. IPX4-rated design. 1-meter impact resistance tested. Serialized for positive identification.			
	 Models: Available in international safety orange or high-visibility yellow. <u>Vehicle Mount E-Spot LiteBox System:</u> Includes shoulder strap and vehicle-mountable hard-wired rack. <u>Vehicle Mount E-Spot FireBox System:</u> Vehicle Mount E-Spot LiteBox System plus two (2) user-programmable ultra-bright blue taillight LEDs. <u>Standard E-Spot LiteBox System:</u> Includes shoulder strap, AC and DC charge cords, and charge rack. <u>Standard E-Spot FireBox System:</u> Standard E-Spot LiteBox System plus two (2) user-programmable ultra-bright blue taillight LEDs. <u>Power Failure E-Spot LiteBox System:</u> Includes shoulder strap, AC and DC charge cords, and charge rack plus the sillight LEDs. 			
WARRANTY:	Streamlight's Limited Lifetime Warranty			
APPROVALS:	CE 🖁 Meets applicable United Kingdom and European Community Directives.			
	NFPA Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.			
OPTIONAL ACCESSORIES:	100V, 120V, 230V, or 240V AC (home) and 12VDC (automobile) charge cords, hands-free shoulder strap			

(included with standard + VM models), locking charge rack, quick-release shoulder/waist strap

	FL1 STANDARD	HIGH	LOW
OUTPUT	342	1500 LUMENS	350 LUMENS
RUN TIME	\bigcirc	11h	28h
DISTANCE	Ν	663m	316m
INTENSITY		110,000 cd	25,000 cd