

PRODUCT FACT SHEET

E-SPOT® LITEBOX® // E-SPOT® FIREBOX®

RECHARGEABLE LED LANTERN

DESCRIPTION: The E-Spot® LiteBox® and FireBox® deliver 1,500 lumens and 110,000 candela of focused light. The lithium-ion

battery provides enhanced performance in a lightweight device. The large tactile push-button switch (with built-in battery status indicator) and a large grip area make this lantern easy to use, even with gloved hands. This light is also easy to carry, whether it's by hand or with the heavy-duty shoulder strap. The articulating head and ability to stand the light upright allows the user to aim light right where it's needed. The E-Spot® models use four (4) LEDs with deep parabolic reflectors for a long-range, focused beam pattern. The LiteBox®

is also available in a Power Failure version.

CASE MATERIAL: High-impact ABS thermoplastic.

DIMENSIONS: Length: 11.2 in (28.4 cm) Width: 5.0 in (12.7 cm) Height: 6.4 in (16.3 cm)

WEIGHT: 3.1 lbs. (1389 g)

LENS: Unbreakable polycarbonate with scratch-resistant coating.

LIGHT SOURCE: Four (4) high-power LEDs, impervious to shock with a 50,000-hour lifetime.

Two (2) ultra-bright blue taillight LEDs (FireBox® models only).

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity.

ON/OFF: Push-button with integrated battery charge indicator. Press and hold to cycle through the different modes.

RUN TIME: See chart.

BATTERY: Lithium-ion 7.2V, 6800 mAh with onboard safety control, rechargeable up to 500 times. Recharges in 7 hours

with provided power supplies. Red and green LEDs in the push-button indicate battery status. When operating,

flashing red indicates charging is needed. When charging, green indicates fully charged.

FEATURES: Cool white LED technology for extreme brightness.

IPX4-rated design.

1-meter impact resistance tested. Serialized for positive identification.

Models: Available in international safety orange or high-visibility yellow.

<u>Vehicle Mount E-Spot LiteBox System:</u> Includes shoulder strap and vehicle-mountable hard-wired rack.

<u>Vehicle Mount E-Spot FireBox System:</u> Vehicle Mount E-Spot LiteBox System plus two (2) user-programmable ultra-bright blue taillight LEDs.

Standard E-Spot LiteBox System: Includes shoulder strap, AC and DC charge cords, and charge rack.

Standard E-Spot FireBox System: Standard E-Spot LiteBox System plus two (2) user-programmable ultra-bright

blue taillight LEDs.

Power Failure E-Spot LiteBox System: Includes shoulder strap, AC and DC charge cords, and charge rack plus

"smart" power failure circuitry that automatically turns the lantern on when the power goes off.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS: CE WA Meets applicable United Kingdom and European Community Directives.

NFPA Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

BC CEC Compliant.

OPTIONAL ACCESSORIES:

100V, 120V, 230V, or 240V AC (home) and 12VDC (automobile) charge cords, hands-free shoulder strap

(included with standard + VM models), locking charge rack, quick-release shoulder/waist strap

OUTPUT
RUN TIME
DISTANCE

INTENSITY

1500 350 LUMENS LUMENS

8.5h 20h

663m 316m

110,000 25,000 cd

All performance claims tested to ANSI/PLATO FL1-2019 Standard

Rev. 4

Issued: 04/01/2010 Revised: 07/17/2025