

## E-FLOOD® LITEBOX® // E-FLOOD® FIREBOX®

### RECHARGEABLE LED LANTERN

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                         |                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|--------------------------|
| <b>DESCRIPTION:</b>   | The E-Flood® LiteBox® and FireBox® deliver 1,500 lumens and 4,700 candela of diffused light. The lithium-ion battery provides enhanced performance in a lightweight device. The large tactile push-button switch (with built-in battery status indicator) and a large grip area make this lantern easy to use, even with gloved hands. This light is also easy to carry, whether it's by hand or with the heavy-duty shoulder strap. The articulating head and ability to stand the light upright allows the user to aim light right where it's needed. The E-Flood® models use four (4) LEDs with shallow reflectors for a widened beam pattern. The LiteBox® is also available in a Power Failure version. |                         |                          |
| <b>CASE MATERIAL:</b> | High-impact ABS thermoplastic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                         |                          |
| <b>DIMENSIONS:</b>    | Length: 11.2 in (28.4 cm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Width: 5.0 in (12.7 cm) | Height: 6.4 in (16.3 cm) |
| <b>WEIGHT:</b>        | 3.1 lbs. (1389 g)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                         |                          |
| <b>LENS:</b>          | Unbreakable polycarbonate with scratch-resistant coating.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                         |                          |
| <b>LIGHT SOURCE:</b>  | Four (4) high-power LEDs, impervious to shock with a 50,000-hour lifetime.<br>Two (2) ultra-bright blue taillight LEDs (FireBox® models only).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                         |                          |
| <b>LIGHT OUTPUT:</b>  | See chart. Optimized electronics provide regulated intensity.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                         |                          |
| <b>ON/OFF:</b>        | Push-button with integrated battery charge indicator. Press and hold to cycle through the different modes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                         |                          |
| <b>RUN TIME:</b>      | See chart.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                         |                          |
| <b>BATTERY:</b>       | Lithium-ion 7.2V, 6800 mAh with onboard safety control, rechargeable up to 500 times. Recharges in 7 hours with provided power supplies. Red and green LEDs in the push-button indicate battery status. When operating, flashing red indicates charging is needed. When charging, green indicates fully charged.                                                                                                                                                                                                                                                                                                                                                                                             |                         |                          |

**FEATURES:**


Cool white LED technology for extreme brightness.  
IPX4-rated design.  
1-meter impact resistance tested.  
Serialized for positive identification.

**Models:** Available in international safety orange or high-visibility yellow.

Vehicle Mount E-Flood LiteBox System: Includes shoulder strap and vehicle-mountable hard-wired rack.

Vehicle Mount E-Flood FireBox System: Vehicle Mount E-Flood LiteBox system plus two (2) user-programmable ultra-bright blue taillight LEDs.

Standard E-Flood LiteBox System: Includes shoulder strap, AC and DC charge cords, and charge rack.

Standard E-Flood FireBox System: Standard E-Flood LiteBox system plus two (2) user-programmable ultra-bright blue taillight LEDs.

Power Failure E-Flood LiteBox System: Includes shoulder strap, AC and DC charge cords, and charge rack plus "smart" power failure circuitry that automatically turns the lantern on when the power goes off.

|                   |                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>WARRANTY:</b>  | Streamlight's Limited Lifetime Warranty                                                                                                                                                                                                                                                                                                                             |
| <b>APPROVALS:</b> |  Meets applicable United Kingdom and European Community Directives.<br><b>NFPA</b> Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.<br> CEC Compliant. |

**OPTIONAL ACCESSORIES:**

100V, 120V, 230V, or 240V AC (home) and 12VDC (automobile) charge cords, hands-free shoulder strap (included with standard + VM models), locking charge rack, quick-release shoulder/waist strap

|           | FL1 STANDARD                                                                        | HIGH                  | LOW                  |
|-----------|-------------------------------------------------------------------------------------|-----------------------|----------------------|
| OUTPUT    |  | <b>1500</b><br>LUMENS | <b>350</b><br>LUMENS |
| RUN TIME  |  | <b>8.5h</b>           | <b>20h</b>           |
| DISTANCE  |  | <b>137m</b>           | <b>63m</b>           |
| INTENSITY |  | <b>4700cd</b>         | <b>1000cd</b>        |