



HID LITEBOX®
RECHARGEABLE HIGH INTENSITY SEARCH LIGHT

MARKET

APPLICATIONS: Fire & Rescue, Military, Utilities, Law Enforcement, Industrial Safety, Sporting Goods.

DESCRIPTION: The HID LiteBox® is a heavy-duty, rechargeable, completely portable high intensity search light. It produces a focused beam of light measuring 1 Million candlepower that illuminates objects 1 mile away and ample peripheral illumination to light an entire scene. Integral D-rings allow attachment of the included heavy duty shoulder strap. Included flood lens or optional IR pass filter attaches to elastomer lens ring.

CASE MATERIAL: High-impact ABS thermoplastic housing. Elastomer impact bumper, lens ring and cushioned grip/handle. Weatherproof construction.

DIMENSIONS: Length: 14.9 in. (38 cm) Body Width: 5.1 in. (13 cm) Overall Height: 8.8 in. (23 cm)
Head Diameter: 7.7 in. (20 cm)

WEIGHT: 10.1 lbs (4.6 kg) with battery (included in purchase).

LENS: Glass. Adhesive sealed to reflector.

LIGHT SOURCE: 35 Watt High Intensity Discharge Xenon lamp with 2000 hour minimum lifetime.

LIGHT OUTPUT: 35 Watt High Intensity Discharge Xenon lamp in a deep-dish parabolic reflector produces a long range high intensity beam with optimum peripheral illumination for scene lighting. Fully articulating head can be aimed precisely at target.
Xenon H.I.D. Lamp Rating: 3350 Lumens typical with 1,000,000 Peak Beam Candlepower.




ON/OFF: Toggle switch allows operation from internal battery or continuous operation from external 12VDC power source.

RUN TIME: 1.75 hours per charge. All models include a 10 foot 12VDC external power cord for continuous operation.

BATTERY: Zero-maintenance 12V, 7.0Ah sealed lead acid and is rechargeable up to 500 times using existing LiteBox® system charge racks. Red and green LEDs provide charge status feedback. 10 hour charge to 90% battery capacity with continuous trickle charge to maximize battery capacity. HID LiteBox® battery will continue to charge while operating directly from an external 12V DC power source when using the remote cord.

MODELS: Standard System - International safety orange or black; includes shoulder strap; comes with AC and DC chargers, 10ft 12VDC power cord, charge rack and flood lens; ideal for field maintenance, inspection of construction sites and remote equipment.
Vehicle Mount System - International safety orange or black; comes with vehicle-mountable hard-wire rack, 10ft 12VDC power cord, flood lens and shoulder carrying strap; ideal for military operations and general scene lighting.

FEATURES: 1,000,000 peak beam candlepower for long range applications.
Serialized for positive identification.
Fits existing Streamlight LiteBox® chargers.

APPROVALS:   Meets applicable United Kingdom and European Community Directives
NFPA Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position
 CEC compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: 100V, 230V, or 240V AC (home) and 12V DC (automobile) charger cords.
Locking charge rack; Quick release shoulder/waist strap.
IR pass filter; flood lens.