

STINGER® CLASSIC LED RECHARGEABLE FLASHLIGHT
MARKET
APPLICATIONS: Law Enforcement, Sporting Goods, Security, Fire & Rescue, Hardware/Tool, Automotive, Industrial, Consumer

DESCRIPTION: Compact & extremely powerful, the Stinger® Classic LED rechargeable flashlight is sized similar to the original Stinger®, but with a C4® LED. It additionally offers 3 microprocessor controlled intensity modes and strobe mode.

CASE MATERIAL: 6000 series machined aircraft aluminum.

DIMENSIONS: Length: 7.65 in. (19.43 cm) Diameter: Major Diameter: 1.60 in. (4.06 cm)
Body Diameter: 1.08 in. (2.74 cm)

WEIGHT: 11.1 oz (315 grams) with battery (included in purchase).

LENS: Custom acrylic optic. Gasket sealed.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See Chart. Optimized electronics provides regulated intensity.
Custom optic design provides a smooth beam with optimum peripheral illumination.

ON/OFF: Multi-function, easy access head mounted push-button switch designed for extremely long life; tested at 1 million actuations.

RUN TIME: See Chart. All claims to 10% of initial lumen output. Strobe: 7.50 continuous hours.

BATTERY: 3-cell, 3.6 Volt, 2.6Ah NiMH sub-C battery, rechargeable up to 1000 times.


CHARGE HOLDERS: Fits existing Stinger® chargers and new Smart chargers.
Steady charger: Fully recharges within 16 hours.
Smart charger: Fully recharges within 4.5 hours (5V/1A USB input) or 3 hours (12VDC input).
Smart PiggyBack® charger: Fully recharges within 7.5 hours (5V/1A USB input) or 4 hours (12VDC input).

CHARGE CORDS: Streamlight universal AC input voltage, 5V/1A USB or 12.7V/.8A output charge cords available with IEC Type A (US & Japan), Type C (Euro), Type G (UK) or Type I (Australia) plugs.
12VDC cigarette lighter or direct wire automotive cords.





FEATURES: C4® LED technology for extreme brightness.
IPX4 Rated for water resistant operation.
1 meter impact resistance tested.
Serialized for positive identification.
LED Charge-continuity indicator on charger base.
Compact, snap-in charger mounts in any position.

WARRANTY: Streamlight's Limited Lifetime Warranty.

APPROVALS:  Meets applicable European Community Directives.

 CEC Compliant (Smart charger models only)

OPTIONAL ACCESSORIES: Safety wands, ring holder, holster, 2.2Ah Li-Ion battery, 5-unit bank charger, Smart charger, Steady charger or Smart Piggy-Back® charger that allows for simultaneous charging of light and battery.

	FL 1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		500 LUMENS	260 LUMENS	130 LUMENS
RUN TIME		2h 45min	5h 30min	10h
DISTANCE		230m	161m	111m
INTENSITY		13,200cd	6,500cd	3,100cd

