

## PRODUCT FACT SHEET

## TLR-3®

## COMPACT RAIL MOUNTED TACTICAL LIGHT

**MARKET** 

**APPLICATIONS:** Law Enforcement, Security, Sporting Goods, Consumer

**DESCRIPTION:** Ultra lightweight & compact, the TLR-3® Weapon-Mounted Tactical Light features the latest in

C4® LED technology and provides 1.5 hours of continuous runtime from a single lithium battery.

Rail clamp designed to rapidly attach/detach from side of weapon.

Models also available for H&K USP Compact frame and H&K USP Full Size frame.

**CASE MATERIAL:** Body: Impact resistant Engineering polymer. Available in black.

Facecap: 6000 series machined aircraft aluminum with black anodized finish.

**DIMENSIONS:** Length: 2.71 in. (6.88 cm) Width: 1.18 in. (3.00 cm) Height: 1.51 in. (3.84 cm)

**WEIGHT:** 2.32 oz (65.8 grams) with battery (included with purchase).

**LENS:** Borofloat high temperature glass.

**LIGHT SOURCE:** C4® LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** 170 lumens, 3,300 candela peak beam intensity and 115 m beam distance.

Smooth parabolic reflector produces a concentrated beam with optimum peripheral illumination.

Optimized electronics provide regulated intensity.

**ON/OFF:** Ambidextrous momentary/steady On-Off switch.

**RUN TIME:** 1.5 continuous hours to the 10% output level.

BATTERY: One (1) 3 Volt CR2 lithium battery, with a storage life of 10 years.

**FEATURES:** Ultra lightweight and compact.

C4® LED technology.

Ambidextrous momentary/steady On-Off switch.

One handed snap-on and tighten interface keeps hands away from muzzle when

attaching/detaching.

Securely fits a broad range of weapons using key kit provided.

Extensively live-fire tested.

Operating temperature: -40°F to +120°F.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

Serialized for positive identification.

**APPROVALS:** ( Meets applicable European Community Directives.

**WARRANTY:** Streamlight's Limited lifetime warranty.

OPTIONAL

ACCESSORIES: Mounting adapters

## PERFORMANCE CURVE

