



**TLR-2 HL®**

**HIGH-LUMEN, WEAPON-MOUNTED TACTICAL LIGHT WITH RED LASER**

- DESCRIPTION:** Lightweight, compact, high-lumen tactical light with integrated red aiming laser featuring the latest in high-power LED technology. The tethered battery door and latch mechanism prevent battery door loss while providing easy battery replacement. Rail clamp designed to rapidly attach/detach from the side of your weapon. User-enabled strobe mode.
- CASE MATERIAL:** 6000 Series machined aircraft aluminum with black anodized finish on main body. High-impact, chemically resistant engineering polymer laser housing.
- DIMENSIONS:** Length: 3.39 in (8.61 cm)      Width: 1.47 in (3.73 cm)      Height: 1.83 in (4.64 cm)
- WEIGHT:** 4.88 oz (138.4 g) with batteries (included in purchase).
- LENS:** High-temperature, shock-mounted, impact-resistant BOROFLOAT® glass; white gasket-sealed glass.
- LIGHT SOURCE:** High-power white LED, impervious to shock with a 50,000-hour lifetime. 640-660nm red laser.
- LIGHT OUTPUT:** 1,000 lumens, 20,000 candela peak beam intensity, and 283m beam distance. TIR optic produces a concentrated beam with optimum peripheral illumination. Laser provides long-range targeting. Optimized electronics provide regulated intensity.
- ON/OFF:** Ambidextrous momentary/steady on-off switch. Three-position mode selector switch (LED only, Laser only, LED/Laser Combo) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.
- RUN TIME:** LED Only - 1.5 hours to 10% output  
Laser Only - 45 hours  
LED/Laser Combo - 1.5 hours to 10% output
- BATTERY:** Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years.
- FEATURES:** High-power LED for extreme brightness. Ambidextrous momentary/steady on-off switch. Operating temperature: -40°F to +120°F. One-handed “snap-on & tighten” interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Includes keys for GLOCK®-style, MIL-STD-1913 (Picatinny), Beretta® 90-TWO, Smith & Wesson® 99/TSW, and SIG SAUER® P320® rails. Extensively live-fire tested impact-resistant construction. Windage & elevation adjustment screws mounted in bushings for long life & dependable zero retention. Highly accurate sight repeatability when remounting. IPX4-rated design for water-resistant operation. Serialized for positive identification.
- APPROVALS:**  Meets applicable United Kingdom and European Community Directives
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** Mounting adapters, remote switches, filters (not recommended for use with contour remotes)

All rights reserved. BOROFLOAT® is a registered trademark of SCHOTT AG.

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations (“EAR”). The exported sale, transfer, or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export, or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.