

TLR-2 HL® G**HIGH-LUMEN, WEAPON-MOUNTED TACTICAL LIGHT WITH GREEN LASER SIGHT**

DESCRIPTION:	The ultimate in target engagement enhancement, this rugged, high-lumen, lithium battery powered weapon light with integrated green laser fits most handguns and long guns. This light/laser combo features a fast and tool-less rail clamp for rock solid repeatability on a wide variety of weapons. Its best-in-class lumen output delivers a powerful beam with extensive range, wide peripheral coverage, and a user-programmable strobe mode. The daylight visible green targeting laser uses the latest direct drive diode that burns brightly in extreme temperatures.		
CASE MATERIAL:	6000 Series machined aircraft aluminum with black anodized finish on main body. High-impact, chemically resistant engineering polymer laser housing.		
DIMENSIONS:	Length: 3.39 in (8.61 cm)	Width: 1.47 in (3.73 cm)	Height: 1.83 in (4.64 cm)
WEIGHT:	4.88 oz (138.4 g) with batteries (included in purchase).		
LENS:	High temperature, shock-mounted, impact-resistant BOROFLOAT® glass; white gasket-sealed glass.		
LIGHT SOURCE:	High-power LED, white, impervious to shock with a 50,000-hour lifetime. Laser: 510-530nm direct drive green laser with wide operating temperature range.		
LIGHT OUTPUT:	1,000 lumens, 20,000 candela peak beam intensity, and 283m beam distance. TIR optic produces a concentrated beam with optimum peripheral illumination. Green laser provides high-visibility, long-range targeting. Optimized electronics provide regulated intensity.		
ON/OFF:	Ambidextrous momentary/steady on-off switch. Three-position mode selector switch (LED only, Laser only, LED/Laser Combo) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.		
RUN TIME*:	LED Only - 1.5 hours to 10% output Laser Only - 17 hours LED/Laser Combo - LED 1.5 hours to 10% output; Laser 1.25 hours		
BATTERY:	Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years		
FEATURES:	High-power LED for extreme brightness. High-visibility green laser with wide operating temperature. Operating temperature: -40°F to +120°F. One-handed “snap-on & tighten” interface keeps hands away from muzzle when attaching/detaching. Mounts directly to handguns with GLOCK®-style rails and to all MIL-STD-1913 (Picatinny) rails. <ul style="list-style-type: none">- Includes keys for GLOCK®-style, Picatinny, Beretta® 90-TWO, Smith & Wesson® 99/TSW, and SIG SAUER® P320® rails. Extensively live-fire tested, impact-resistant construction. Windage & elevation adjustment screws mounted in bushings for long life & dependable zero retention. Highly accurate sight repeatability when remounting. IPX4-rated design for water-resistant operation. Serialized for positive identification.		
APPROVALS:	 Meets applicable United Kingdom and European Community Directives		
WARRANTY:	Streamlight's Limited Lifetime Warranty		
ACCESSORIES:	Mounting adapters, remote switches, filters (not recommended for use with contour remotes)		

* Run times are approximations and contingent upon various factors, encompassing battery manufacturer specifications, storage temperature conditions, operational temperatures, and operation of light.

All rights reserved. BOROFLOAT® is a registered trademark of SCHOTT AG.

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations (“EAR”). The exported sale, transfer, or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export, or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.