

PROTAC® RAIL MOUNT 2

DESCRIPTION:	Lightweight, low-profile, gun-mounted tactical light powered by two (2) CR123A lithium batteries. The two (2) CR123A batteries provide 2 hours of continuous run time on high and over 20 hours on low. The rail clamp is designed to securely attach/detach from rifles, carbines, and submachine guns with a MIL-STD-1913 rail. The included M-LOK® mount allows for alternative mounting options to M-LOK and M-LOK compatible rail systems.		
CASE MATERIAL:	6000 Series machined aircraft aluminum with black anodized finish		
DIMENSIONS:	Length: 5.00 in (12.7 cm)	Width: 1.20 in (3.04 cm)	Height: 1.50 in (3.81 cm)
WEIGHT:	5.0 oz (141.7 g) with batteries (included in purchase)		
LENS:	High-temperature, shock-mounted, AR coated, impact-resistant BOROFLOAT® glass		
LIGHT SOURCE:	White LED impervious to shock with a 50,000-hour lifetime		
LIGHT OUTPUT:	High - 625 lumens; 22,000 candela peak beam intensity; 297 m beam distance Low - 60 lumens; 2,000 candela peak beam intensity; 89 m beam distance TIR optic produces a concentrated beam with optimum peripheral illumination.		
ON/OFF:	Multi-function, push-button tactical tail switch or dual remote pressure switch with latching push-button. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch to allow for user selection of one of three different programs: high/strobe (factory default), high only, or low/high.		
RUN TIME:	High - 1.5 hours of regulated run time and 2 hours to 10% output Low - 18 hours of regulated run time and 21 hours to 10% output Solid-state current regulation for consistent illumination level.		
BATTERY:	Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years		
FEATURES:	Push-button tail switch features momentary/constant on operation One-handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching from the firearm Securely fits a broad range of weapons Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK and M-LOK compatible rail systems Extensively live fire tested, impact-resistant construction IP67-rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes IP54 rated with remote pressure switch installed		
APPROVALS:	CE UK Meets applicable United Kingdom and European Community Directives (BC) CEC Compliant		
WARRANTY:	Streamlight's Limited Lifetime Warranty		
OPTIONAL ACCESSORIES:	Red, blue, and green filters		