

STRION® DS
HIGH PERFORMANCE DUAL SWITCH RECHARGEABLE FLASHLIGHT
MARKET
APPLICATIONS: Premium Professional Light - Law Enforcement, Industrial, Security, Outdoor, Consumer

DESCRIPTION: Ultra compact & powerful, the Strion® DS rechargeable flashlight offers two independent easy to locate switches, 3 microprocessor controlled variable intensity modes, strobe mode and the latest in power LED technology. The Strion® DS also offers three different user selectable programs. The combination of rechargeable batteries and high power LED results in one of the lowest operating costs of any flashlight made.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: Length: 6.40 in. (16.26 cm) Head Diameter: 1.25 in. (3.18 cm)
 Barrel Diameter: 0.95 in. (2.41 cm) Diameter at Tri-Lobe Anti-Roll Flange: 1.35 in. (3.43 cm)

WEIGHT: 5.4 oz (153 grams) with battery

LENS: Borofloat High Temperature Glass. Gasket sealed.

LIGHT SOURCE: High power LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

ON/OFF: Multi-function, easy-access head mounted push-button switch and second multi-function push-button tactical tailswitch where both switches offer full feature control independent of each other. One handed operation of momentary, variable intensity or strobe mode using either switch. Switches designed for extremely long life; tested at 1 million actuations. TEN-TAP® programmable switch allows user selection of one of three different programs: high/medium/low with strobe (factory default), high only without strobe, or high/medium/low without strobe.

RUN TIME:  See chart. All claims to 10% of initial lumen output. Strobe: 5 continuous hours.

BATTERY: Lithium Ion with on-board safety control circuit, 3.63V, 2600mAh, rechargeable up to 1000 times.

CHARGING: Fits existing Strion® chargers.
 Clamp style charge holder with digital control circuit that prevents overcharge.
 Fully recharges battery in 3.5 hours and charges battery in product.
 Charge base LED indication: LED Steady - Charging; LED Blinking - Charged.

FEATURES: High power LED for extreme brightness.
 IPX4 rated design; water resistant operation.
 2 meter impact resistance tested.
 TEN-TAP® programmable switch allows user to select one of three different programs.
 LED Charge-continuity indicator on charger base.
 Compact, snap-in charger mounts in any position.
 Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty.

APPROVALS:  Meets applicable European Community directives.
 CEC Compliant

OPTIONAL ACCESSORIES: Color Filters, Safety Wands, Holster, Rail Mount, Piggyback® Charger, 6 Unit Bank Charger.

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		375 LUMENS	150 LUMENS	40 LUMENS
RUNTIME		2h 30min	6h 15min	24h
DISTANCE		219m	141m	72m
INTENSITY		12,000cd	5,000cd	1,300cd

