



**PROTAC® RAIL MOUNT HL-X // PROTAC® RAIL MOUNT HL-X USB**

- DESCRIPTION:** High candela, extreme beam reach, high lumen, gun-mounted tactical light. Both the ProTac Rail Mount HL-X and HL-X USB models offer two switch configurations – a push-button tactical switch or the remote pressure option allow for momentary or constant on operation. The rail clamp is designed to securely attach to rifles, carbines, and submachine guns with a MIL-STD-1913 rail or with the included M-LOK® mount allowing for alternative mounting options to M-LOK® and M-LOK® compatible rail systems. The light is powered by CR123A lithium batteries or Streamlight's rechargeable SL-B26® battery pack.
- CASE MATERIAL:** 6000 Series machined aircraft aluminum with black anodized finish
- DIMENSIONS:** Length: 5.43 in (13.8 cm)      Width: 1.45 in (3.68 cm)      Height: 1.72 in (4.37 cm)
- WEIGHT:** 6.4 oz (181.4 g) with CR123A batteries  
6.9 oz (195.6 g) with SL-B26 rechargeable battery pack
- LENS:** High-temperature, shock-mounted, AR coated, impact-resistant BOROFLOAT® glass
- LIGHT SOURCE:** White LED impervious to shock with a 50,000-hour lifetime
- LIGHT OUTPUT:** High: 1,000 lumens; 50,000 candela peak beam intensity; 447m beam distance  
Low: 60 lumens; 3,100 candela peak beam intensity; 111m beam distance  
  
Solid state current regulation for consistent illumination level and the reflector produces a concentrated beam with optimum peripheral illumination.
- ON/OFF:** Multi-function, push-button tactical tail switch or dual remote pressure switch with latching push-button. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch to allow for user selection of one of three different programs: high/strobe (factory default), high only, or low/high.
- RUN TIME:** SL-B26:    High: 1.75 hours  
                  Low: 24 hours  
                  Strobe: 3.5 hours  
  
CR123A:    High: 1.25 hours  
                  Low: 21 hours  
                  Strobe: 2.5 hours
- BATTERY:** Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years. Also accepts one (1) Streamlight SL-B26® lithium-ion rechargeable battery pack.
- FEATURES:** Push-button tail switch features momentary/constant on operation  
One-handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching from the firearm  
Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK® compatible rail systems  
Extensively live fire tested, impact-resistant construction  
IP67-rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes  
IP54-rated with remote pressure switch installed for water-resistant operation
- APPROVALS:**   Meets applicable United Kingdom and European Community Directives  
 CEC Compliant
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** Battery charge cradles, replacement batteries

All rights reserved. M-LOK® is a registered trademark of Magpul Industries Corp. BOROFLOAT® is a registered trademark of SCHOTT AG.