

DUALIE® RECHARGEABLE
DUAL FUNCTION INTRINSICALLY SAFE RECHARGEABLE FLASHLIGHT

DESCRIPTION: The Dualie® Rechargeable is an intrinsically safe, high performance, Li Ion battery powered dual function LED flashlight. The Dualie® Rechargeable features a forward facing LED spot beam and a side facing LED flood light that can be used individually or at the same time for enhanced safety. Light has opposing switches for easy user activation of desired function(s). Body features a superior grip texture to provide a comfortable but slip resistant feel and is constructed of an engineered polymer resin that is virtually indestructible, shock resistant, non-conductive and light weight. Integrated, non-protruding spring loaded belt clip contained within body outline. All models available with optional belt clip with two integrated magnets.

CASE MATERIAL: Impact and chemical resistant Engineered Polymer resin; gasket sealed and vented. Available in high visibility yellow or black.

DIMENSIONS: Length: 7.00 in. (17.78 cm) Length w/Magnetic clip: 7.50 in. (19.05 cm)
 Body thickness: 1.06 in. (2.69 cm) Body Width: 1.52 in. (3.86 cm) Face cap diameter: 1.86 in. (4.72 cm)

WEIGHT: Standard clip: 6.8 oz. (193 grams)
 Magnetic clip: 7.09 oz. (201 grams)

LENS: Unbreakable polycarbonate facecap and side lens with scratch resistant coating.

LIGHT SOURCE: Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: Spot - 230 lumens, 15,000 candela peak beam intensity and 245 meter beam distance.
 Flood - 110 lumens, 70 candela peak beam intensity and 17 meter beam distance.
 Spot and Flood combined - 325 lumens.

ON/OFF: Opposing head switches for easy identification. Spot LED push button head switch provides momentary or constant operation. Flood LED push button head switch provides on/off operation.

RUN TIME: Spot - 10 hours to 10% of initial lumen output. See performance curve.
 Flood - 20 hours to 10% of initial lumen output.
 Both - 7 hours to 10% initial lumen output.

CHARGE HOLDER: Fully recharges within 10 hours.

CHARGE CORD: Streamlight universal AC input voltage, 5V/1A USB output charge cord available with IEC Type A (US & Japan), Type C (Euro), Type G (UK), or IEC Type I (Australia) plugs.

BATTERY: One 3300mAh lithium ion battery.

FEATURES: Dual function with opposing switches for easy function identification.




2 meter impact resistance tested.


IP67 rated; dust-tight and waterproof to 1 meter for 30 minutes.

Spot beam utilizes smooth parabolic reflector for tight beam with optimum peripheral illumination.

Integrated, spring loaded belt clip contained within body outline.

Corrosion proof.

APPROVALS:  Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; CL I, ZN 0, IIC; T-Code: T4

  Meets applicable United Kingdom and European Community Directives

 CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL ACCESSORIES: N/A

