

## POLYTAC 90™ LED LITHIUM POWER RIGHT ANGLE POLYMER FLASHLIGHT

**MARKET:** Fire & Rescue, Sporting Goods, Law Enforcement, Security, Hardware/Tool, Industrial, Consumer

**DESCRIPTION:** The PolyTac 90™ LED is a super bright and compact right angle personal light with C4®LED technology. This light offers microprocessor controlled high and low intensity modes, strobe mode and integrated carabiner style D-ring for a variety of attachment methods. Operates on CR123A Lithium primary cells.

**CASE MATERIAL:** High impact super tough nylon polymer for exceptional durability and sure grip. All openings o-ring sealed for water resistance. Available in black and yellow.

**DIMENSIONS:** Height: 5.22 in. (13.3 cm)      Head Diameter: 1.25 in. (3.18 cm)      Body Diameter: 1.00 in. (2.54 cm)

**WEIGHT:** 4.1 oz (116 grams) with batteries (included in purchase)

**LENS:** Glass lens, gasket sealed.

**LIGHT SOURCE:** C4®LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See chart. Optimized electronics provide regulated intensity.  
Textured parabolic reflector produces a smooth beam hotspot with optimum peripheral illumination to aid in navigation.



**RUN TIME:** See chart. All claims to 10% of initial lumen output.  
Strobe: 6 continuous hours.



**ON/OFF/MODE:** Head mounted push button switch provides one handed momentary or constant "on" operation. Fast double click from "off" to activate Strobe mode; fast triple click from "off" to activate Low mode.

**BATTERIES:** Two (2) 3 Volt CR123A Lithium batteries with a shelf life of 10 years.

**FEATURES:** C4®LED technology for extreme brightness.  
90 degree head.



1 meter impact resistance tested.  
IPX7 rated design; waterproof to 1 meter for 30 minutes.  
Integrated carabiner style D-ring for a variety of attachment methods.  
Fully rotatable/reversible/removable clip to allow a variety of mounting positions.  
LED Solid State Power Regulation provides maximum light output throughout battery life.  
Individually serialized for positive identification.

**APPROVALS:** Meets applicable European Community Directives. **CE**  
Meets requirements of NFPA 1971-8.6 (2007).

**WARRANTY:** Streamlight's Limited Lifetime Warranty warrants this product to be free of defect, including the LED, for a lifetime of use. We will repair, replace or refund the purchase price, at our option, of any Streamlight product that does not work as a result of a manufacturing defect for as long as you own it. This limited lifetime warranty excludes abuse, batteries, switches, electronics and normal wear and tear. Switches and electronics have a two (2) year warranty with proof of purchase.

**OPTIONAL ACCESSORIES:** N/A

	FL 1 STANDARD	HIGH	LOW
OUTPUT	170 LUMENS	170 LUMENS	17 LUMENS
RUNTIME	3h 45min	3h 45min	30h
DISTANCE	167m	167m	53m
INTENSITY	7,000cd	7,000cd	700cd

Strobe Runtime: 6 hours

