

TLR-7®/TLR-7®A
COMPACT RAIL MOUNTED TACTICAL LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Sporting Goods, Consumer

DESCRIPTION: Ultra lightweight & compact, the **TLR-7®** or **TLR-7®A** Weapon-Mounted Tactical Light features the latest in LED technology for high lumen operation and provides 1.5 hours of continuous runtime from a single lithium battery. 500 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. The **TLR-7®** model has side switches while the **TLR-7®A** model has rear switches. Rail clamp designed to rapidly attach/detach from side of weapon.

CASE MATERIAL: Body and Facecap: 6000 Series machined aircraft aluminum with black anodized finish.
Switch housing: Impact and chemical resistant engineered polymer.

DIMENSIONS: Width: 1.18 in. (2.98 cm) Height: 1.27 in. (3.22 cm)
Length: **TLR-7®:** 2.15 in. (5.46 cm) **TLR-7®A:** 2.58 in. (6.55 cm)

WEIGHT: 2.40 oz. (68.1 grams) with battery (included with purchase).

LENS: High temperature, shock mounted, impact resistant Borofloat® glass.

LIGHT SOURCE: LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: 500 lumens, 5,000 candela peak beam intensity and 140 m beam distance.
Custom TIR optic produces a concentrated beam with optimum peripheral illumination.
Optimized electronics provide regulated intensity.

ON/OFF: **TLR-7®:** Left and right side switches provide ambidextrous operation.
TLR-7®A: Rear switches left and right of trigger guard provide ambidextrous operation available with high and low actuators.
Quick press for constant on operation and press and hold for momentary operation.
Double tap either switch within ¼ second activates strobe (if enabled).

RUN TIME: 1.5 continuous hours to the 10% output level.

BATTERY: One (1) 3 Volt CR123A lithium battery, with a storage life of 10 years.

FEATURES: Ultra lightweight and compact.
High power LED for extreme brightness.
Ambidextrous operation.
One handed snap-on and tighten interface keeps hands away from muzzle when attaching or detaching.
Securely fits a broad range of weapons using key kit provided.
Extensively live-fire tested.
Operating temperature: -40°F to +120°F.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Serialized for positive identification.

APPROVALS:  Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited lifetime warranty.

OPTIONAL

ACCESSORIES: Mounting adapters

NOTE: Switch housings are not interchangeable between **TLR-7®** side switch and **TLR-7®A** rear switch models.