

## PRODUCT FACT SHEET

## USB HAZ-LO® INTRINSICALLY SAFE HEADLAMP

**DESCRIPTION:** The USB Haz-Lo<sup>®</sup> Headlamp is an intrinsically safe, high performance, rechargeable headlamp

that features two power LEDs. There are a total of three output modes, Spot, Flood and Spot/Flood Combo for maximum brightness. The flood LED is strategically placed high on the light for shadow free lighting when mounted on a hard hat. The headband design is optimized for

easy removal for cleaning.

CASE MATERIAL: Tough thermoplastic construction with elastomer button. Available in Safety Yellow.

DIMENSIONS: Height: 1.72 in. (4.36 cm) Width: 3.25 in. (8.25 cm) Depth: 1.75 in (4.45 cm)

**WEIGHT:** 4.1 oz (116.2 grams) with battery. (Battery included with purchase)

**LENS:** Unbreakable polycarbonate lenses.

**LIGHT SOURCE:** Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** Spot - 190 lumens, 2,000 candela peak beam intensity and 89 meter beam distance.

Flood - 120 lumens, 90 candela peak beam intensity and 19 meter beam distance.

Spot/Flood Combined - 250 lumens.

**ON/OFF:** Push button switch. Click the switch to step through each mode, Spot, Flood, Spot/Flood Combo,

and OFF.

**RUN TIME:** See performance curve.

Spot - 11 hours to 10% of initial lumen output. Flood - 21 hours to 10% of initial lumen output.

Spot/Flood Combined - 10 hours to 10% of initial lumen output.

**BATTERY:** One 3300 mAh lithium ion battery. Mechanical battery polarity protected.

CHARGING: Digital control circuit that prevents overcharge. Charge indication LED: Red - Charging; Green -

Charged.

Fully recharges the battery in 10 hours with Streamlight AC charger. Charge time will vary when

using the USB cord connected to a computer or other power source.

**FEATURES:** Spot beam utilizes a smooth parabolic reflector for a tight beam with optimum peripheral

illumination.

Flood beam placement is designed to allow for shadow free operation when on a hard hat.

Micro USB charge port under rubber cover.

IP67 rated; dust-tight and waterproof to 1 meter for 30 minutes.

2 meter impact resistance tested.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS: Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; CL 1, Zn 0, IIC; T-Code: T4

C 는 Meets applicable United Kingdom and European Community Directives

BC CEC Compliant

OPTIONAL

**ACCESSORIES:** Rubber head strap

PERFORMANCE CURVE

250
3POT & FLOOD COMBO

190
5POT
120

FLOOD

FLOOD

120
1122 13 14 15 16 17 18 19 20 2

**Issued:** 04/17/2019

**Revised:** 09/11/2025 **Rev** 2 Made in China. **Document #335**