



ENDURO® PRO USB
LI POLYMER BATTERY-POWERED HEADLAMP

MARKET

APPLICATIONS: Outdoor, Sporting Goods, Automotive, Hardware/Do-It-Yourself, Industrial, Emergency Medical Services, Safety, Gift, Consumer, Pest Control, Boating

DESCRIPTION:

The Enduro® Pro USB headlamp features two power LEDs and a total of six output modes. Three levels each for spot and flood. Battery charging is effortless, just pull open the rubber USB cover and plug in the charge cord. Charge indication is provided with red for charging and green for charged on the front of the light. The headband design is also optimized for easy cleaning.

CASE MATERIAL:

Tough Polycarbonate thermoplastic construction with elastomer over mold. Easy color change from Black to Safety Yellow with the snap on color cover.

DIMENSIONS:

Height: 1.85 in. (4.70 cm) Width: 2.19 in. (5.56 cm) Front to Back: 1.7 in (4.32 cm)

WEIGHT:

3.6 oz (102.0 grams) with Lithium battery.

LENS:

Unbreakable polycarbonate lens.

LIGHT SOURCE:

Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT:

See charts for white light.



ON/OFF:

Multi-function push button switch. Low, Medium, High and Off

To change the lights beam from Spot to Flood, Turn on the light, then press and hold the on/off button for two seconds until the light changes to flood. Release the button. To go back to the Spot beam, repeat the press and hold process again.

Switching Output Modes: Pushing the button within 1.5 seconds of the last button push will change the light mode. You may sequence through all light levels and then to off.

NOTE: If you wait more than two seconds between button pushes, the next press of the button will turn the light off.

RUN TIME:



See charts. All claims to 10% of initial lumen output.

BATTERY:

2000 mAh lithium polymer cell. Recharges in approximately 4 hours (dependent of output port voltage).

FEATURES:



LED technology for extreme brightness.
USB to micro USB charge cord.
45° tilting head.
IPX4 rated for water resistant operation.
2 meter impact resistance tested.

WARRANTY:

Streamlight's Limited Lifetime Warranty

APPROVALS:

Meets applicable European Community directives. **CE**

OPTIONAL

ACCESSORIES:

Rubber head strap, Dual lock

	SPOT			FLOOD				
	FL1 STANDARD	HIGH	MEDIUM	LOW	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		200 LUMENS	90 LUMENS	25 LUMENS		145 LUMENS	50 LUMENS	15 LUMENS
RUNTIME		6h 15min	19h	48h		7h	21h	48h
DISTANCE		91m	60m	32m		30m	18m	11m
INTENSITY		2,080cd	890cd	250cd		220cd	80cd	30cd

