



TLR-7® X CONTOUR REMOTE

MULTI-FUEL, RAIL-MOUNTED TACTICAL LIGHT WITH GRIP SWITCH

DESCRIPTION:	The TLR-7® X Contour Remote weapon-mounted light features multi-fuel capability - powered by either one (1) CR123A or one (1) Streamlight SL-B9™ lithium-ion rechargeable battery, delivering up to 725 lumens and 9,500 candela. The light includes customizable rear paddle switches, as well as a contoured remote switch that activates naturally when using a firing grip. This unit has two models available for GLOCK® (fits most railed Gen 4/Gen 5 handguns) or SIG SAUER® (fits P320® XCarry frame).
CASE MATERIAL:	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish Switch housing: Impact- and chemical-resistant engineered polymer
DIMENSIONS:	Width: 1.16 in (2.95 cm) Height: 1.79 in (4.55 cm) Length: 4.6 in (11.68 cm)
WEIGHT:	CR123A: 2.69 oz (76.3 g) with battery. SL-B9: 2.85 oz (80.7g) with battery.
LENS:	High-temperature, shock-mounted, impact-resistant BOROFLOAT® glass
LIGHT SOURCE:	White LED, impervious to shock with a 50,000-hour lifetime
LIGHT OUTPUT:	SL-B9®: 725 lumens, 9,500 candela peak beam intensity, and 195m beam distance. CR123A: 550 lumens, 7,200 candela peak beam intensity, and 170m beam distance. Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity.
ON/OFF:	Rear switches left and right of trigger guard provide ambidextrous operation. Momentary and constant on operation. User-activated strobe.
RUN TIME:	CR123A: 1.5 continuous hours to the 10% output level SL-B9: 1 hour continuous operation to the 10% output level
BATTERY:	CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years. SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Battery installed/removed through facecap. No need to remove from firearm. Charges within 2.5 hours via USB-C cord or optional bank charger.
FEATURES:	Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A. High-power LED for extreme brightness. Ambidextrous operation. One-handed snap-on and tighten interface keeps hands away from muzzle when installing. Securely fits select GLOCK® and SIG SAUER® handguns. Extensively live fire tested. Operating temperature: -40°F to +120°F (CR123A) or -4°F to +120°F (SL-B9®). IPX7-rated design; waterproof to 1 meter for 30 minutes. Serialized for positive identification.
APPROVALS:	 Meets applicable United Kingdom and European Community Directives  CEC Compliant  TAA Compliant
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	Mounting adapters, HPL face cap, SL-B9 Bank Charger

All rights reserved. GLOCK® and SIG SAUER® are registered trademarks of Glock, Inc. and SIG Sauer, Inc., respectively. Streamlight has not sought endorsement of this product from Glock, Inc. or SIG Sauer, Inc.

BOROFLOAT® is a registered trademark of SCHOTT AG.

Issued: 12/03/2020

Revised: 01/16/2026 Rev: 3

Assembled in the USA.

Document #366