

**PROTAC® 2.0 RAIL MOUNT**  
**RECHARGABLE, HIGH LUMEN LONG GUN LIGHT**

<b>DESCRIPTION:</b>	The ProTac® 2.0 Rail Mount is a 2,000-lumen tactical weapon-mounted flashlight that uses a proprietary Streamlight SL-B50® protected Li-Ion rechargeable battery pack. It features a tactical tail cap switch for momentary or constant on operation and three different user-selectable programs. A remote pressure switch option is also available. The SL-B50® charges directly via USB-C port in the body of the battery pack. The battery is keyed to ensure proper alignment of the charging port. USB-C cord included.
<b>CASE MATERIAL:</b>	6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black.
<b>DIMENSIONS:</b>	Length: 6.30 in (16 cm)      Head Diameter: 1.46 in (3.7 cm)      Body Diameter: 1.02 in (2.6 cm)
<b>WEIGHT:</b>	9.06 oz (257 g) with (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery pack (included in purchase).
<b>LENS:</b>	Glass with anti-reflective coating; gasket-sealed
<b>LIGHT SOURCE:</b>	LED technology, impervious to shock with a 50,000-hour lifetime
<b>LIGHT OUTPUT:</b>	High: 2,000 lumens, 17,700 candela peak beam intensity, 266 m beam distance. Low: 250 lumens, 2,150 candela peak beam intensity, 93 m beam distance. Fully regulated output for consistent lumen performance over the entire battery life.
<b>ON/OFF:</b>	Multi-function, push-button tail switch with momentary and latching constant on operations. Optional remote switch available in momentary only and momentary/latching versions. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe (factory default), high only, or low/high.
<b>RUN TIME:</b>	High: 2.5 hours; Low: 11 hours; Strobe: 4.5 hours All run time claims are to 10% of initial output.
<b>BATTERY:</b>	(1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery pack with on-board safety control, 4,900mAh. Recharges in 6 hours.
<b>FEATURES:</b>	LED technology for extreme brightness. IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes. IPX4-rated with the remote pressure switch installed for water-resistant operation. All openings O-ring sealed. 2-meter impact resistance tested. Securely fits a broad range of weapons. Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK® compatible rail systems. Extensively live fire tested, impact-resistant construction. Serialized for positive identification.
<b>APPROVALS:</b>	CE UK Meets applicable United Kingdom and European Community Directives (BC) CEC Compliant
<b>WARRANTY:</b>	Streamlight's Limited Lifetime Warranty
<b>OPTIONAL ACCESSORIES:</b>	USB-C charge cord, remote pressure switch, SL-B50® battery pack