

SURVIVOR® X

HIGH CANDELA, RIGHT ANGLE, FIREFIGHTING LIGHT

DESCRIPTION: The Survivor® X is an intrinsically safe, lightweight, handheld flashlight with a right-angle head designed for use in hazardous locations. This light features a low-profile bezel length to minimize snag hazards. Its large translucent button with LED battery status indicator provides gloved access to microprocessor-controlled high and low intensity modes and emergency flash. Optional Smoke Cutter® optic technology offers insertable black or amber plugs for user-customizable beam pattern.

CASE MATERIAL: Housing, base, and battery housing made from high-impact, super tough nylon offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in international safety orange and high-visibility yellow.

DIMENSIONS: Height: 7.06 in (17.9 cm) Width: 2.85 in (7.24 cm) Diameter: 2.32 in (5.89 cm)
 Height in charger: 8.67 in (22.0 cm)
 Grip area: Height: 3.60 in (9.14 cm) Width: 2.20 in (5.59 cm) Thickness: 1.35 in (3.43 cm)

WEIGHT: Li-Ion: 12.2 oz (346 g) * Alkaline: 12.8 oz (363 g) * SL-B26®: 11.9 oz (337 g) *

LENS: Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy-duty bezel. O-ring sealed.

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity.
 Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination.
 Optional Smoke Cutter® insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.


ON/OFF: Ultrasonic welded push-button switch designed for extremely long life. Translucent rubber dome push-button actuator provides easy operation even when wearing heavy gloves.

RUN TIME: See chart. All claims to 10% of initial lumen output. Flash: 8 hours continuous.

BATTERY: 2.6Ahr Li-Ion battery pack rechargeable up to 1,000 times; available with 120/230/240VAC systems. Fully charges in 5 hours. Charger indicator turns red when charging, turns green when fully charged. One (1) optional Streamlight SL-B26® protected Li-Ion USB-rechargeable battery pack. Three (3) optional AA alkaline batteries.

BATTERY STATUS INDICATOR: The translucent switch boot contains an integrated red/green battery status indicator.
 Solid green for 5 seconds: Battery is ready for use
 Solid red: 45 minutes or less of battery life remaining
 Flashing red: 15 minutes or less of battery life remaining

FEATURES: Updated battery door design for improved operation and seal
 Translucent switch boot with integrated battery status indicator
 Updated charge cradle for one-handed light removal
 Multi-fuel design
 IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes
 2-meter impact resistance tested
 Serialized for positive identification

APPROVALS:**  Class I & II, Division 1, Groups A, B, C, D, E, F, G; Class III, T-Code: T3/T4
 T-CLASS T4 only: Streamlight 90341, Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91/L91
 T-CLASS T3 only: Streamlight 90340, Energizer E91, Rayovac No. 815
 Class I & II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 only with Streamlight 220115













** See product for specific ratings.

NFPA Flashlight meets 500°F requirements of NFPA 1970 - 14.2 (2025).
 Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

CE UK Meets applicable United Kingdom and European Community Directives
(BC) CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

ACCESSORIES: 5-Unit Bank Charger

	Li-Ion Battery Pack			AA Alkaline Batteries			SL-B26® USB Battery Pack		
	FL1 STANDARD	HIGH	LOW	FL1 STANDARD	HIGH	LOW	FL1 STANDARD	HIGH	LOW
OUTPUT		250 LUMENS	60 LUMENS		250 LUMENS	60 LUMENS		250 LUMENS	60 LUMENS
RUN TIME		3h 45min	15h		5h	15h		4h	15h
DISTANCE		447m	237m		447m	237m		447m	237m
INTENSITY		50,000cd	14,000cd		50,000cd	14,000cd		50,000cd	14,000cd

*With battery (based on model; included in purchase)
 All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 06/13/2022

Revised: 06/04/2025

Rev: 3

Assembled in the USA.

Document #386