

## SURVIVOR® X

### HIGH CANDELA, RIGHT ANGLE, FIREFIGHTING LIGHT

**DESCRIPTION:** The Survivor® X is an intrinsically safe, lightweight, handheld flashlight with a right-angle head designed for use in hazardous locations. This light features a low-profile bezel length to minimize snag hazards. Its large translucent button with LED battery status indicator provides gloved access to microprocessor-controlled high and low intensity modes and emergency flash. Optional Smoke Cutter® optic technology offers insertable black or amber plugs for user-customizable beam pattern.

**CASE MATERIAL:** Housing, base, and battery housing made from high-impact, super tough nylon offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in international safety orange and high-visibility yellow.

**DIMENSIONS:** Height: 7.06 in (17.9 cm) Width: 2.85 in (7.24 cm) Diameter: 2.32 in (5.89 cm)  
 Height in charger: 8.67 in (22.0 cm)  
 Grip area: Height: 3.60 in (9.14 cm) Width: 2.20 in (5.59 cm) Thickness: 1.35 in (3.43 cm)

**WEIGHT:** Li-Ion: 12.2 oz (346 g) \* Alkaline: 12.8 oz (363 g) \* SL-B26®: 11.9 oz (337 g) \*

**LENS:** Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy-duty bezel. O-ring sealed.

**LIGHT OUTPUT:** See chart. Optimized electronics provide regulated intensity.  
 Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination.  
 Optional Smoke Cutter® insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.

**ON/OFF:** Ultrasonic welded push-button switch designed for extremely long life. Translucent rubber dome push-button actuator provides easy operation even when wearing heavy gloves.

**RUN TIME:** See chart. All claims to 10% of initial lumen output. Flash: 8 hours continuous.

**BATTERY:** 2.6Ahr Li-Ion battery pack rechargeable up to 1,000 times; available with 120/230/240VAC systems. Fully charges in 5 hours. Charger indicator turns red when charging, turns green when fully charged. One (1) optional Streamlight SL-B26® protected Li-Ion USB-rechargeable battery pack. Three (3) optional AA alkaline batteries.

**BATTERY STATUS INDICATOR:** The translucent switch boot contains an integrated red/green battery status indicator.  
 Solid green for 5 seconds: Battery is ready for use  
 Solid red: 45 minutes or less of battery life remaining  
 Flashing red: 15 minutes or less of battery life remaining

**FEATURES:** Updated battery door design for improved operation and seal  
 Translucent switch boot with integrated battery status indicator  
 Updated charge cradle for one-handed light removal  
 Multi-fuel design  
 IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes  
 2-meter impact resistance tested  
 Serialized for positive identification

**APPROVALS\*\*:**  Class I & II, Division 1, Groups A, B, C, D, E, F, G; Class III, T-Code: T3/T4  
 T-CLASS T4 only: Streamlight 90341, Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91/L91  
 T-CLASS T3 only: Streamlight 90340, Energizer E91, Rayovac No. 815  
 Class I & II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 only with Streamlight 220115

\*\* See product for specific ratings.

**NFPA** Flashlight meets 500°F requirements of NFPA 1970 - 14.2 (2025).  
 Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

**CE UK** Meets applicable United Kingdom and European Community Directives  
**(BC)** CEC Compliant

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**ACCESSORIES:** 5-Unit Bank Charger

|           | Li-Ion Battery Pack                                                                 |            |           | AA Alkaline Batteries                                                               |            |           | SL-B26® USB Battery Pack                                                              |            |           |
|-----------|-------------------------------------------------------------------------------------|------------|-----------|-------------------------------------------------------------------------------------|------------|-----------|---------------------------------------------------------------------------------------|------------|-----------|
|           | FL1 STANDARD                                                                        | HIGH       | LOW       | FL1 STANDARD                                                                        | HIGH       | LOW       | FL1 STANDARD                                                                          | HIGH       | LOW       |
| OUTPUT    |  | 250 LUMENS | 60 LUMENS |  | 250 LUMENS | 60 LUMENS |  | 250 LUMENS | 60 LUMENS |
| RUN TIME  |  | 3h 45min   | 15h       |  | 5h         | 15h       |  | 4h         | 15h       |
| DISTANCE  |  | 447m       | 237m      |  | 447m       | 237m      |  | 447m       | 237m      |
| INTENSITY |  | 50,000cd   | 14,000cd  |  | 50,000cd   | 14,000cd  |  | 50,000cd   | 14,000cd  |

\*With battery (based on model; included in purchase)  
 All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 06/13/2022

Revised: 06/04/2025 Rev: 3

Assembled in the USA.

Document #386