

## **SURVIVOR® X ATEX**

### **HIGH CANDELA, RIGHT ANGLE, FIREFIGHTING LIGHT**

**DESCRIPTION:** The Survivor® X ATEX is an intrinsically safe, lightweight, handheld flashlight with a right-angle head designed for use in hazardous locations. This light features a low-profile bezel length to minimize snag hazards. Its large translucent button with LED battery status indicator provides gloved access to microprocessor-controlled high and low intensity modes and emergency flash. Optional Smoke Cutter® optic technology offers insertable black or amber plugs for user-customizable beam pattern.

**CASE MATERIAL:** Housing, base, and battery housing made from high-impact, super tough nylon offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting.


**DIMENSIONS:**

Height: 7.06 in (17.9 cm)	Width: 2.85 in (7.24 cm)	Diameter: 2.32 in (5.89 cm)
Height in charger: 8.67 in (22.0 cm)		
Grip area: Height: 3.60 in (9.14 cm)	Width: 2.20 in (5.59 cm)	Thickness: 1.35 in (3.43 cm)

**WEIGHT:** Li-Ion: 12.2 oz (346 g) \*      AA Alkaline: 12.8 oz (363 g) \*

**LENS:** Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy-duty bezel. O-ring sealed.

**LIGHT OUTPUT:** See chart. Optimized electronics provide regulated intensity. Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination. Optional Smoke Cutter® insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.



**ON/OFF:** Ultrasonic welded push-button switch designed for extremely long life. Translucent rubber dome push-button actuator provides easy operation even when wearing heavy gloves.

**RUN TIME:** All claims to 10% of initial lumen output. Flash: 8 hours continuous.

**BATTERY:** 2.6Ahr Li-Ion battery pack rechargeable up to 1,000 times; available with 120/230/240VAC systems. Fully charges in 5 hours. Charger indicator turns red when charging, turns green when fully charged. Three (3) optional AA alkaline or lithium batteries.


**BATTERY STATUS INDICATOR:** The translucent switch boot contains an integrated red/green battery status indicator.  
Solid green for 5 seconds: Battery is ready for use  
Solid red: 45 minutes or less of battery life remaining  
Flashing red: 15 minutes or less of battery life remaining

**FEATURES:**

- Translucent switch boot with integrated battery status indicator
- Updated charge cradle for one-handed light removal
- IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes
- 2-meter impact resistance tested
- Serialized for positive identification



**APPROVALS\*\*:**

 SGS22ATEX0081; BAS22UKEX0222; IECEx BAS22.0045  
II 1G Ex ia IIC T3/T4 Ga; II 2D Ex ib IIIB T270°C Db  
T-CLASS T4: Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91  
T-CLASS T3: Streamlight pack 90340, Energizer E91, Rayovac No. 815

\*\* See product for specific ratings.











DNV 24.0248  
Ex ia IIC T4/T3 Ga; Ex ib IIIB T270°C Db  
T-Class T4: Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91  
T-Class T3: Streamlight pack 90340, Energizer E91, Rayovac No. 815

**NFPA** Flashlight meets 500°F requirements of NFPA 1970 - 14.2 (2025).  
Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

**CE UK** Meets applicable United Kingdom and European Community Directives.

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**ACCESSORIES:** 5-Unit Bank Charger

	Li-Ion Battery Pack			AA Battery		
	FL 1 STANDARD	HIGH	LOW	FL 1 STANDARD	HIGH	LOW
OUTPUT		250 LUMENS	60 LUMENS		250 LUMENS	60 LUMENS
RUN TIME		3h 45min	15h		5h	15h
DISTANCE		447m	237m		447m	237m
INTENSITY		50,000cd	14,000cd		50,000cd	14,000cd

\*With battery (based on model; included in purchase)  
All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 06/13/2022

Revised: 06/04/2025

Rev: 4

Assembled in the USA.

Document #387