PRODUCT FACT SHEET

SURVIVOR® X ATEX

DESCRIPTION: The Survivor® X ATEX is an intrinsically safe, lightweight, handheld flashlight with a right-angle head designed for use in hazardous locations. This light features a low-profile bezel length to minimize snag hazards. Its large translucent button with LED battery status indicator provides gloved access to microprocessor-controlled high and low intensity modes and emergency flash. Optional Smoke Cutter® optic technology offers insertable black or amber plugs for user-customizable beam pattern.

CASE MATERIAL: Housing, base, and battery housing made from high-impact, super tough nylon offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting.

DIMENSIONS: Height: 7.06 in (17.9 cm) Width: 2.85 in (7.24 cm) Diameter: 2.32 in (5.89 cm)
Height in charger: 8.67 in (22.0 cm)
Grip area: Height: 3.60 in (9.14 cm) Width: 2.20 in (5.59 cm) Thickness: 1.35 in (3.43 cm)

WEIGHT: Li-Ion: 12.2 oz (346 g) * AA Alkaline: 12.8 oz (363 g) *

LENS: Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy-duty bezel. O-ring sealed.

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity.
Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination.
Optional Smoke Cutter® insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.

ON/OFF: Ultrasonic welded push-button switch designed for extremely long life. Translucent rubber dome push-button actuator provides easy operation even when wearing heavy gloves.

RUN TIME: All claims to 10% of initial lumen output. Flash: 8 hours continuous.

BATTERY: 2.6Ahr Li-Ion battery pack rechargeable up to 1,000 times; available with 120/230/240VAC systems.
Fully charges in 5 hours. Charger indicator turns red when charging, turns green when fully charged.
Three (3) optional AA alkaline or lithium batteries.
WARNING – EXPLOSION RISK, BURN, AND FIRE HAZARD. Do not use SL-B9® or SL-B34® batteries in firefighting apparatus or fire situations. Do not expose SL-B9® or SL-B34® battery to temperatures greater than 140˚F (60˚C).

BATTERY STATUS INDICATOR: The translucent switch boot contains an integrated red/green battery status indicator.
Solid green for 5 seconds: Battery is ready for use
Solid red: 45 minutes or less of battery life remaining
Flashing red: 15 minutes or less of battery life remaining

FEATURES: Translucent switch boot with integrated battery status indicator
Updated charge cradle for one-handed light removal
IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes
2-meter impact resistance tested
Serialized for positive identification

APPROVALS:**

** See product for specific ratings.

SGS22ATEX0081; BAS22UKEX0222 *Issue 1*; IECEx BAS22.0045
II 1G Ex ia IIC T3/T4 Ga; II 1D Ex ia IIIC T_{200}131˚C Da
T-CLASS T4: Streamlight pack 90347, Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91
T-CLASS T3: Streamlight pack 90340, Energizer E91, Rayovac No. 815

DNV 24.0248
Ex ia IIC T4/T3 Ga; Ex ib IIIB T270˚C Db
T-Class T4: Duracell MN1500, Panasonic LR6XJ, Varta 4006, Energizer EN91
T-Class T3: Streamlight pack 90340, Energizer E91, Rayovac No. 815

NFPA Flashlight meets 500˚F requirements of NFPA 1970-14.2 (2025).
Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

Meets applicable United Kingdom and European Community Directives.

WARRANTY: Streamlight's Limited Lifetime Warranty

ACCESSORIES: 5-Unit Bank Charger

	Li-Ion Battery Pack		AA Battery	
	HIGH	LOW	HIGH	LOW
OUTPUT	250 LUMENS	60 LUMENS	250 LUMENS	60 LUMENS
RUN TIME	3h 45min	15h	5h	15h
DISTANCE	447m	237m	447m	237m
INTENSITY	50,000cd	14,000cd	50,000cd	14,000cd

* With battery (based on model; included in purchase)
All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 06/13/2022
Revised: 02/20/2026 **Rev:** 5 **Assembled in the USA.** **Document #387**