

**DUALIE® 3AA COLOR-RITE®**

**DESCRIPTION:** The Dualie® 3AA Color-Rite® is an intrinsically safe, high-performance, 3 AA battery powered flashlight that features a dual beam. The spot beam uses a white high-power LED for maximum illumination, while the flood beam uses a 90 CRI LED for true color recognition. It has opposing switches for easy user activation of desired functions. The body features a superior grip texture to provide a comfortable but slip-resistant feel and is constructed of an engineered polymer resin that is virtually indestructible, shock-resistant, non-conductive, and lightweight. The integrated, non-protruding spring-loaded belt clip is contained within the body outline.

**CASE MATERIAL:** Impact- and chemical-resistant engineered polymer resin; gasket-sealed and vented. Class I, Division 1 model available in high visibility yellow. ATEX/IEC model with antistatic body and integrated & retained facecap lock available in international safety orange.

**DIMENSIONS:** Length: 7.00 in. (17.78 cm)                      Facecap diameter: 1.86 in. (4.72 cm)  
Body thickness: 1.06 in. (2.69 cm)                      Body Width: 1.52 in. (3.86 cm)

**WEIGHT:** 6.6 oz (187 g) with AA alkaline batteries, 5.7 oz (162 g) with AA lithium batteries\*

**LENS:** Unbreakable polycarbonate facecap

**LIGHT SOURCE:** One (1) high-power white LED, impervious to shock with a 50,000-hour lifetime  
One (1) 90 CRI LED, impervious to shock with a 50,000-hour lifetime

**LIGHT OUTPUT:** Spot - 225 lumens, 8,000 candela peak beam intensity and 179-meter beam distance  
Flood - 175 lumens, 380 candela peak beam intensity and 39-meter beam distance  
Spot and Flood combined - 320 lumens, 7,000 candela peak beam intensity and 167-meter beam distance


**ON/OFF:** Opposing head switches for easy identification. Spot LED push-button head switch provides one handed momentary or constant operation. Flood LED push-button head switch provides on/off operation.

**RUN TIME:** Spot - 8 hours to 10% of initial lumen output  
Flood - 8.5 hours to 10% of initial lumen output  
Combo - 5 hours to 10% of initial lumen output

**BATTERY:** Three (3) "AA" size alkaline or lithium primary batteries. Mechanical battery polarity protection.

**FEATURES:** Dual function with opposing switches for easy function identification  
2-meter impact resistance tested  
IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes  
Spot beam utilizes smooth parabolic reflector for tight beam with optimum peripheral illumination  
Flood beam uses a 90 CRI LED for true color recognition  
Integrated, spring-loaded belt clip contained within body outline  
Corrosion proof



**APPROVALS\*:**  Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; CL I, ZN 0, IIC; Exia; T-Code: T4 (approved for use with Energizer E91, EA91, L91, Duracell MN1500 and Rayovac NO.815)



II 1G Ex ia op is IIC T3/T4 Ga; FTZU 15ATEX0221X, IECEx FTZU 16.0017X (approved for use with Energizer L91, Duracell MN1500, Rayovac NO.815 (T4); Energizer E91, Panasonic LR6XP & LR6XWA (T3))



Meets applicable European Community Directives

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL ACCESSORIES:** Helmet mount

\* See product for specific ratings.

All performance claims to ANSI/PLATO FL1-2019 Standard

Issued: 07/19/2022

Revised:

Rev: 0

Engineered in the USA, Made in China.

Document #389