



TLR-7® HL-X sub USB

MULTI-FUEL, HIGH-LUMEN, RAIL-MOUNTED LIGHT DESIGNED FOR USE WITH GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X RAIL AND GLOCK® 48 RAIL SUBCOMPACT HANDGUNS

DESCRIPTION:	The TLR-7® HL-X sub USB features 1,000 lumens and 13,000 candela when powered by one (1) Streamlight SL-B9® proprietary lithium-ion rechargeable battery pack. Multi-fuel capability allows for operation with one (1) CR123A battery delivering 550 lumens and 7,300 candela. The specialized clamp system allows for mounting on a GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X rail, or GLOCK® 48 rail. Please refer to streamlight.com for the current compatibility list.				
CASE MATERIAL:	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish. Switch housing: Impact- and chemical-resistant engineered polymer.				
DIMENSIONS:	Width: 1.16 in (2.95 cm)	Height: 1.24 in (3.15 cm)	Length: 2.51 in (6.38 cm)		
WEIGHT:	SL-B9®: 2.49 oz (70.6 g) with battery CR123A: 2.39 oz (67.8 g) with battery				
LENS:	High temperature, shock-mounted, impact-resistant BOROFLOAT® glass.				
LIGHT SOURCE:	White LED, impervious to shock with a 50,000-hour lifetime.				
LIGHT OUTPUT:	SL-B9®: 1,000 lumens, 13,000 candela peak beam intensity, and 228m beam distance (default) or programmable to 550 lumens, 7,300 candela peak beam intensity, and 171m beam distance. CR123A: 550 lumens, 7,300 candela peak beam intensity, and 171m beam distance. Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity.				
ON/OFF:	Rear switches left and right of trigger guard provide ambidextrous operation. Momentary and constant on operation. User-programmable strobe.				
RUN TIME:	SL-B9®: 30 minutes (default) or 1 hour (programmable) continuous operation to 10% output level. CR123A: 1.5 hours continuous operation to 10% output level.				
BATTERY:	SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery with integrated safety circuit, rechargeable up to 500 cycles. Charges within 2.5 hours via USB-C cord or bank charger. CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years.				
FEATURES:	High-lumen operation with SL-B9® Li-Ion rechargeable battery pack. Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A. Ambidextrous operation. Securely fits railed GLOCK® 43X and 48 models. Extensively live fire tested. Operating temperature: -4°F to +120°F (SL-B9®) or -40°F to +120°F (CR123A). IPX7-rated design; waterproof to 1 meter for 30 minutes. Serialized for positive identification.				
APPROVALS:	CE UK CA	Meets applicable United Kingdom and European Community Directives			
	BC	CEC Compliant (with SL-B9® only)			
	TAA	TAA Compliant			
WARRANTY:	Streamlight's Limited Lifetime Warranty				
OPTIONAL ACCESSORIES:	SL-B9® Li-Ion Battery Bank Charger				

All rights reserved. GLOCK® is a registered trademark of Glock, Inc. Streamlight has not sought endorsement of this product from Glock, Inc.

BOROFLOAT® is a registered trademark of SCHOTT AG.