

## PRODUCT FACT SHEET

## SL-SIDESADDLE® UNIVERSAL FIT, HARD HAT, HELMET & HAT LIGHT

**DESCRIPTION:** The SL-SideSaddle is a hands-free lighting system that is lightweight and compact. It is designed to

mount to a wide variety of hard hats, safety helmets and hats, integrating seamlessly without interfering with visors, hearing protection, or other accessories. The SL-SideSaddle has two ultra-bright front LEDs with spot, flood and spot/flood combined beams, as well as a blue rear safety taillight allowing the user to see and be seen for increased safety. Push-button switch with mode memory recalls the last beam setting when turned on. Rear taillight is programmable for function. Powered by 3x AAA batteries.

CASE MATERIAL: Tough polycarbonate thermoplastic construction. Offered in yellow and black.

**DIMENSIONS:** Length: 3 in (7.6 cm) Width: 2.25 in (5.7 cm) Height: 1.14 in (2.9 cm)

WEIGHT: 3.4 oz (95 grams)

LENS: Unbreakable polycarbonate lens.

**LIGHT SOURCE:** Dual LEDs, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT: See chart.

ON / OFF: Push-button tail switch with blue rear LED safety taillight.

**RUN TIME:** See chart.

**BATTERY:** Three (3) AAA alkaline batteries.

**FEATURES:** Universal fit for hats, hard hats and helmets.

> Does not interfere with most hard hat or helmet accessories. Conveniently adjustable for personalized beam placement. Easily removeable for handheld use and battery changes.

IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.

2-meter impact resistance tested.

Ultra bright blue LED safety taillight for enhanced visibility.

Spot, flood, and combination optics for application specific illumination.

CE K Meets applicable United Kingdom and European Community Directives **APPROVALS:** 

(BC) CEC Compliant

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL** 

**ACCESSORIES:** Hard Hat Mounting Base, Universal Y-Straps, Slotted Hard Hat Straps, Hat Mount Kit

SPOT	FLOOD	COMBO

OUTPUT

RUNTIME

DISTANCE

INTENSITY

FL1 STANDARD	HIGH	LOW	FL1 STANDARD
314	250 LUMENS	60 LUMENS	31/2
(	6.75h	12h	()
	100m	53m	
	2,500 cd	715 cd	

HIGH	LOW	FL1 STANDARD	HIGH	LOW
235 LUMENS	60 LUMENS	31/5	300 LUMENS	110 LUMENS
6.5h	16h	(	5h	6.75h
29m	15m		87m	51m
215 cd	55 cd		1,900 cd	660 cd