

SL-SIDESADDLE® UNIVERSAL FIT, HARD HAT, HELMET & HAT LIGHT

DESCRIPTION: The SL-SideSaddle is a hands-free lighting system that is lightweight and compact. It is designed to mount to a wide variety of hard hats, safety helmets and hats, integrating seamlessly without interfering with visors, hearing protection, or other accessories. The SL-SideSaddle has two ultra-bright front LEDs with spot, flood and spot/flood combined beams, as well as a blue rear safety taillight allowing the user to see and be seen for increased safety. Push-button switch with mode memory recalls the last beam setting when turned on. Rear taillight is programmable for function. Powered by 3x AAA batteries.

CASE MATERIAL: Tough polycarbonate thermoplastic construction. Offered in yellow and black.

DIMENSIONS: Length: 3 in (7.6 cm) Width: 2.25 in (5.7 cm) Height: 1.14 in (2.9 cm)

WEIGHT: 3.4 oz (95 grams)

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: Dual LEDs, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT: See chart.

ON / OFF: Push-button tail switch with blue rear LED safety taillight.

RUN TIME: See chart.

BATTERY: Three (3) AAA alkaline batteries.

FEATURES:



Universal fit for hats, hard hats and helmets.
Does not interfere with most hard hat or helmet accessories.
Conveniently adjustable for personalized beam placement.
Easily removable for handheld use and battery changes.
IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.
2-meter impact resistance tested.
Ultra bright blue LED safety taillight for enhanced visibility.
Spot, flood, and combination optics for application specific illumination.

APPROVALS:  Meets applicable United Kingdom and European Community Directives
CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

**OPTIONAL
ACCESSORIES:**

Hard Hat Mounting Base, Universal Y-Straps, Slotted Hard Hat Straps, Hat Mount Kit

	SPOT			FLOOD			COMBO		
	FL1 STANDARD	HIGH	LOW	FL1 STANDARD	HIGH	LOW	FL1 STANDARD	HIGH	LOW
OUTPUT		250 LUMENS	60 LUMENS		235 LUMENS	60 LUMENS		300 LUMENS	110 LUMENS
RUNTIME		6.75h	12h		6.5h	16h		5h	6.75h
DISTANCE		100m	53m		29m	15m		87m	51m
INTENSITY		2,500 cd	715 cd		215 cd	55 cd		1,900 cd	660 cd