

PRODUCT FACT SHEET

SL-SIDESADDLE® USB RECHARGEABLE, UNIVERSAL FIT, HARD HAT, SAFETY HELMET & HAT LIGHT

DESCRIPTION: The SL-SideSaddle USB is a hands-free lighting system that is lightweight and compact. It is designed to

mount to a wide variety of hard hats, safety helmets and hats, integrating seamlessly without interfering with visors, hearing protection, or other accessories. The SL-SideSaddle has two ultra-bright front LEDs with spot, flood and spot/flood combined beams, as well as a blue rear safety taillight allowing the user to see and be seen for increased safety. Push-button switch with mode memory recalls the last beam setting when turned on. Rear taillight is programmable for function. Powered by a lithium polymer

battery, rechargeable using a USB-C cord.

CASE MATERIAL: Tough polycarbonate thermoplastic construction. Offered in yellow and black.

DIMENSIONS: Width: 1.72 in (4.4 cm) Length: 3 in (7.6 cm) Height: 1.14 in (2.9 cm)

WEIGHT: 3.1 oz (88 grams)

Unbreakable polycarbonate lens. LENS:

LIGHT SOURCE: Dual LEDs, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT: See chart.

ON / OFF: Push-button tail switch with blue rear LED safety taillight.

RUN TIME: See chart.

BATTERY: 2000 mAh lithium polymer cell. Recharges in approximately 4 hours (dependent of output port voltage).

FEATURES: Universal fit for hard hats, helmets and hats.

Does not interfere with most hard hat or helmet accessories. Conveniently adjustable for personalized beam placement.

Easily removeable for handheld use and charging.

IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.

2-meter impact resistance tested.

Ultra bright blue LED safety taillight for enhanced visibility.

Spot, flood, and combination optics for application specific illumination.

CE K Meets applicable United Kingdom and European Community Directives **APPROVALS:**

(BC) CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: Hard Hat Mounting Base, Universal Y-Straps, Slotted Hard Hat Straps, Hat Mount Kit,

Lithium Polymer Battery, USB-C cord

OUTPUT

RUNTIME

DISTANCE

INTENSITY

FL1 STANDARD	HIGH	LOW
345	350 LUMENS	100 LUMENS
0	6.25h	12h
M	130m	69m
	4,250 cd	1,200 cd

SPOT

	FLOOD
_	HIGH

FL1 STANDARD	HIGH	LOW
31/5	325 LUMENS	85 LUMENS
0	7h	12h
	35m	17m
	300 cd	75 cd

COMBO

FL1 STANDARD	HIGH	LOW
345	400 LUMENS	160 LUMENS
0	5h	7h
	98m	62m
	2,400 cd	960 cd

Issued: 06/04/2025 Revised: