



PRODUCT FACT SHEET

ProTac® HP-X USB / ProTac® HP-X

MULTI FUEL, HIGH-CANDELA TACTICAL FLASHLIGHT

DESCRIPTION:	The ProTac® HP-X USB and ProTac® HP-X are 800 lumen, 105,000 candela tactical flashlights that use either a proprietary Streamlight® SL-B26® protected Li-Ion USB rechargeable battery or two CR123A disposable batteries. The ProTac® HP-X USB is a complete rechargeable system that comes with a USB-C charge cord and SL-B26® protected Li-Ion USB rechargeable battery pack that features an integrated USB-C charge port. The ProTac® HP-X comes packaged with two CR123A batteries. Both versions feature a tactical tail cap switch for momentary or constant on operation, three different user selectable programs and a pocket clip for convenience. Constructed from high-strength aluminum alloy with a Type II MIL Spec anodized finish for durability and abrasion-resistance. Packaged with a removable pocket clip and holster.
CASE MATERIAL:	6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black.
DIMENSIONS:	Length: 5.55 in. (14.1 cm) Head Diameter: 1.38 in. (3.5 cm) Body Diameter: 0.94 in. (2.4 cm)
WEIGHT:	ProTac® HP-X USB: 5.9 oz (168 grams) with one Streamlight® SL-B26® protected Li-Ion USB rechargeable battery (included in purchase). ProTac® HP-X: 5.4 oz (154 grams) with two CR123A batteries (included in purchase).
LENS:	Glass with anti-reflective coating; gasket sealed.
LIGHT SOURCE:	LED technology, impervious to shock with a 50,000 hour lifetime.
LIGHT OUTPUT:	See chart. Fully regulated output for consistent lumen performance over the battery life.
ON/OFF:	Multi-function, push-button tactical tail switch. One-handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/medium/high.
RUN TIME:	See charts for specific battery type. All runtime claims are to 10% of initial lumen output.
BATTERY:	One (1) Streamlight® SL-B26® protected Li-Ion USB rechargeable battery pack with on-board safety control, 2600mAh, rechargeable up to 500 times. Recharges in 5 hours. Two (2) 3 Volt CR123A lithium batteries with a storage life of 10 years.
FEATURES:	LED technology for extreme brightness. IP68 rated; dust tight and waterproof to 2 meters. All openings o-ring sealed. 2-meter impact resistance tested. Multi fuel; accepts one SL-B26® Li-Ion battery pack or two CR123A batteries. TEN-TAP® programmable switch allows user to select one of three different programs. Anti-roll face cap. Serialized for positive identification. Unbreakable pocket clip and Holster.
APPROVALS:	CE Meets applicable European Community Directives. BC CEC Compliant (ProTac® HP-X USB only)
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	Holster, Charge cords.



	WITH CR123A BATTERIES			
	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		800 LUMENS	240 LUMENS	45 LUMENS
RUNTIME		1h30min	4h15min	24h
DISTANCE		648m	369m	159m
INTENSITY		105,000cd	34,000cd	6,300cd

Strobe Run Time: 3 Hr

	WITH SL-B26® RECHARGEABLE BATTERY			
	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		800 LUMENS	240 LUMENS	45 LUMENS
RUNTIME		2h	5h	31h
DISTANCE		648m	369m	159m
INTENSITY		105,000cd	34,000cd	6,300cd

Strobe Run Time: 4 Hr 15 Min

All performance claims to ANSI/PLATO FL1-2019 Standard

Issued: 05/09/2025

Revised:

Rev: 0

Made In China

Document #438