

ProTac® 2.0 HP




HIGH-CANDELA / HIGH-LUMEN RECHARGEABLE FLASHLIGHT

- DESCRIPTION:** The ProTac® 2.0 HP is a 2,000 lumen, high-candela tactical flashlight that uses a proprietary Streamlight SL-B50® protected Li-Ion rechargeable battery. The ProTac® 2.0 HP features a tactical tail cap switch for momentary or constant on operation and three different user-selectable programs. The Streamlight SL-B50® charges directly via USB-C port in the body of the battery. The battery is keyed to ensure proper alignment of the charging port. Packaged with a USB-C cord, removable pocket clip and holster.
- CASE MATERIAL:** 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black.
- DIMENSIONS:** Length: 6.10 in. (155mm) Head Diameter: 1.46 in. (37 mm) Body Diameter: 1.02 in. (26 mm)
- WEIGHT:** 8.25 oz (234 grams) with (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery (included in purchase)
- LENS:** Glass with anti-reflective coating; gasket-sealed
- LIGHT SOURCE:** LED technology, impervious to shock with a 50,000-hour lifetime
- LIGHT OUTPUT:** See chart. Fully regulated output for consistent lumen performance over the entire battery life
- ON/OFF:** Multi-function, push-button tactical tail switch with momentary and latching constant on operations. One-handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only or low/medium/high.
- RUN TIME:** See chart below. All run time claims are to 10% of initial lumen output.
- BATTERY:** One (1) Streamlight SL-B50® protected 4,900mAh Li-Ion USB-rechargeable battery with on-board safety control. Recharges in 6 hours.

FEATURES:







LED technology for extreme brightness
 IP67 rated; dust-tight and waterproof to 1 meter for 30 minutes.
 All openings O-ring sealed.
 2-meter impact resistance tested
 Anti-roll face cap
 Serialized for positive identification

- APPROVALS:**   Meets applicable European Community Directives
 CEC Compliant

- WARRANTY:** Streamlight's Limited Lifetime Warranty

- OPTIONAL ACCESSORIES:** Holster, USB-C charge cord, SL-B50® battery

OUTPUT:

FL 1 STANDARD	HIGH	MEDIUM	LOW
	2000 LUMENS	550 LUMENS	100 LUMENS
	2h 30m	5h	31h
	583m	300m	132m
	85,000cd	22,500cd	4,400cd

Strobe Run Time: 2h